

## ZH350ST

Ultra-compact high brightness Full HD 1080p laser projector









- Bright Full HD 1080p DuraCore laser projector -3500 lumens and IP6X certified
- Ultra compact and short throw lens for easy installation - 360-degree and portrait projection
- DuraCore laser technology 30,000 hours maintenance-free laser light source
- Designed with the environment in mind -DuraCore laser technology cuts power consumption and ensures a long product lifespan



The ZH350ST is one of Optoma's most compact, hassle free Full HD 1080p DuraCore laser projectors to date. This short throw 3500-lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it 34% smaller than the previous generation, offering flexible installation in virtually any orientation and location.

## **Specifications**

EAN: 5055387666795, Colour: White

UPC: 796435 44 657 4, Colour: White

Display/image

Display technology DLP™

**Resolution** 1080p Full HD (1920x1080)

 Brightness
 3,500 lumens

 Contrast ratio
 300,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3,16:9,16:10

 Keystone correction +/-30°

horizontal

Keystone correction - vertical +/-30°

Has vertical auto keystone Yes correction

 $\begin{array}{lll} \textbf{Displayable colours (millions)} & 1073.4 \\ \textbf{Horizontal scan rate} & 15 \sim 140 \text{Khz} \\ \textbf{Vertical scan rate} & 24 \sim 120 \text{Hz} \\ \textbf{Uniformity} & 75\% \\ \end{array}$ 

**Screen size** 0.76m ~ 7.62m (30" ~ 300") diagonal

Lamp info
Light source type
Laser
LASER life
30,000 hours

 Optical
 0.496:1

 Throw ratio
 0.496:1

 Projection distance (m)
 0.3m - 3.3m

 Togetair distance (ii)
 0.5iii - 0.5ii

 Zoom type
 Manual

 Focal length (mm)
 7.51

 Native offset
 116%

Connectivity Connections

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

 General
 32dB

 Noise level (typical)
 34dB

 Noise level (max)
 34dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)

**3D compatibility**Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D 720p50 / 60

3D ready

Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese Yes

24/7 operationYes360° operationYes

**Operating conditions** 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 15W

 In the box
 AC power cord

Remote control
2x AAA batteries
Basic user manual

Input lag 8.60ms
Optional wireless models UHDCast Pro

Power

**Power supply** 100V ~ 240V, 50-60Hz

 Power consumption (standby)
 <0.5W</td>

 Power consumption (min)
 98W

 Power consumption (max)
 139W

Weight and dimensions

 $\begin{array}{ll} \textbf{Dimensions (W x D x H) mm} & 274 \times 216 \times 114 \\ \textbf{Gross weight} & 4.2 \text{ kg} \\ \textbf{Net weight} & 3 \text{ kg} \\ \end{array}$ 





