


HD28i

Big screen sports entertainment









- Ideal for daytime sports viewing Powerful 4000 lumens
- Amazing colour Bring the match to life with bright vivid images
- Easy connectivity HDMI and USB power

reactions.

• All-in-one solution - Built-in audio for ultimate convenience

Immerse yourself in the game with the HD28i and experience every moment on the big screen. Convenient and easy to set up, this compact

high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting Amazing colour technology, it delivers accurate true-to-life colour reproduction for sports and movie lovers. It also has low input latency - perfect for games and fast-moving events that rely on rapid



Specifications

Resolution 1080p Full HD (1920x1080)

 Brightness
 4,000 lumens

 Contrast ratio
 50,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3

 Keystone correction - vertical
 +/-40°

 Horizontal scan rate
 15.3 ~ 91.1Khz

 Vertical scan rate
 24 ~ 85(120 for 3D)Hz

Uniformity 75%

Screen size 0.85m ~ 7.77m (33.5" ~ 306") diagonal

Lamp info
Light source type Lamp
Lamp watts 220

Lamp life hours (up to) 5000 (Bright), 6500 (Dynamic), 6000 (Eco), 7000 (Eco+),

10000 (Education)

Lamp life (education) 10,000 hours

 Optical
 1.47:1 ~ 1.63:1

 Projection distance (m)
 1.2m - 10m

| 1.211 | 1011 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 | 2007 |

Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

x Composite video, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D

support + MHL

Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-

A power 1A

Control 1 x RS232

 General
 Noise level (typical)
 29dB

 Noise level (max)
 31dB

 PC compatibility
 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

 2D compatibility
 NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibilitySide-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italiar

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

 Operating conditions
 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

 Remote control
 Card style

 Remote control
 Card

 Speaker count
 1

 Watts per speaker
 2W

In the box AC power cord
Remote control

Remote control
Battery
Basic user manual

Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit,

WHD200

 Power

 Power supply
 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 204W

 Power consumption (max)
 266W

Weight and dimensions

 Dimensions (W x D x H) mm
 298 x 230 x 96

 Gross weight
 3.31 kg

 Net weight
 2.82 kg





