

HD29HSTx

Bright short throw home entertainment projector



- **Lights on viewing - 4000 lumens for use any time of day**
- **Short throw lens - 100" image from just over a metre away**
- **4K UHD and HDR compatible - Enhanced detail for an immersive viewing experience**
- **Lightning-fast gaming projector - Supports 1080p 120Hz with 8.4ms response time**



Project a 100" image from just over a metre away with the bright HD29HSTx short throw projector. Feel the action and experience every moment on the big screen for immersive gaming, live sports and movies.

Convenient and easy to set up this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting HDR and Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers.

Specifications

EAN: 5055387666436, Colour: White



Display/image

Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	4,000 lumens
Contrast ratio	50,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	70%
Screen size	0.92m ~ 7.82m (36.2" ~ 307.8") diagonal

Lamp info

Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Optical

Throw ratio	0.49:1
Projection distance (m)	0.4m - 3.4m
Focal length (mm)	7.42
Native offset	116%

Connectivity

Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232
-------------	--

General

Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

Operating conditions

5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control

Data remote with laser and mouse function

Speaker count

1

Watts per speaker

10W

In the box

AC power cord
Remote control
2x AAA batteries
Basic user manual

Optional wireless models

WHD200

Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	200W
Power consumption (max)	285W

Weight and dimensions

Dimensions (W x D x H) mm	316 x 244 x 108
Gross weight	3.99 kg
Net weight	3.99 kg

