

ZW403

Compact high brightness laser projector



- **Bright WXGA DuraCore laser projector - 4500 ANSI lumens**
- **Versatile - 1.3x zoom, 360-degree and portrait projection**
- **Ultimate control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **30,000 hours maintenance-free laser light source**

The ZW403 is a compact WXGA DuraCore IP6X laser projector. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation. Its small and lightweight footprint, 1.3x zoom combined with 360-degree and portrait projection make it a breeze to install.

This feature-packed projector is 4K and HDR compatible, has a built-in speaker and its laser technology delivers up to 30,000 hours maintenance-free laser light source. For ultimate control, the projector comes with RJ45 connection allowing you to monitor and control your network in multiple rooms.

Geared for medium-sized exhibition venues, events, tradeshows or meeting rooms, it maintains excellent image quality as brightness and colour saturation is preserved for longer compared to lamp systems.

Specifications

| | |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display/image | |
| Display technology | DLP |
| Resolution | WXGA (1280x800) |
| Brightness | 4,500 lumens |
| Contrast ratio | 300,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 4:3,16:9 |
| Keystone correction - vertical | +/-40° |
| Has vertical auto keystone correction | Yes |
| Displayable colours (millions) | 1073,4 |
| Horizontal scan rate | 15.375 ~ 91.146 KHz |
| Vertical scan rate | 50 ~ 85 Hz (120Hz for 3D)Hz |
| Uniformity | 85% |
| Screen size | 0,76m ~ 7,65m (30" ~ 301") diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 1,18:1 ~ 1,54:1 |
| Projection distance (m) | 1m - 7,7m |
| Zoom | 1,3 |
| Zoom type | Manual |
| Focal length (mm) | 16.901 ~ 21.6076 |
| Native offset | 113% |
| Connectivity | |
| Connections | Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x micro USB service |
| General | |
| Noise level (typical) | 30dB |
| Noise level (max) | 32dB |
| PC compatibility | UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP6X |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 24/7 operation | Yes |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Data remote with laser and mouse function |
| Speaker count | 1 |
| Watts per speaker | 10W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | UHDCast Pro |
| Networking | |
| LAN - control | Yes |
| Power | |
| Power supply | 100V ~ 240V, 50-60Hz |
| Power consumption (standby) | <0.5W |
| Power consumption (min) | 157W |
| Power consumption (max) | 211W |
| Weight and dimensions | |
| Net weight | 5,5kg |
| Dimensions (W x D x H) mm | 337 x 265 x 122,5 |

