

# HZ41HDR

Compact high brightness Full HD laser home projector



- **Bright 4400 lumens for lights on viewing - Full HD 1080p laser projector, 4K UHD and HDR compatible**
- **Eco-friendly design - Low power consumption, energy saving and a long product lifespan**
- **Optoma Smart App - Control this projector and make quick and easy image adjustments all from your mobile device**
- **Low input lag - Supports 1080p 120Hz at 8.4ms and 4K 60Hz at 16.7ms for responsive gaming and viewing**



The HZ41HDR is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4400-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.<sup>1</sup>

Use Optoma's latest SmartApp to make quick adjustments to your setup and take advantage of low latency gaming mode for lightning quick response times.

# Specifications

EAN: 5055387600607, Colour: Black



## Display/image

Display technology	DLP®
Resolution	1080p Full HD (1920x1080)
Brightness	4,400 lumens
Contrast ratio	2,500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9, 16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal

## Lamp info

Light source type	Laser
LASER life	30,000 hours

## Optical

Throw ratio	1.48:1 ~ 1.62:1
Projection distance (m)	1m - 10m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.86 ~ 24mm
Native offset	116%

## Connectivity

Connections	<b>Inputs</b> 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm <b>Outputs</b> 1 x Audio 3.5mm, 2 x USB-A power 1.5A <b>Control</b> 1 x RS232, 1 x 12V trigger, 1 x RJ45, 1 x 3D sync
-------------	--

## General

Noise level (min)	29dB
Noise level (max)	31dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2500m
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual

## Power

Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	110W
Power consumption (max)	150W

## Weight and dimensions

Dimensions (W x D x H) mm	274 x 216 x 114
Gross weight	4.3 kg
Net weight	2.9 kg