

**XS1**

InFocus Xseries

## Get close!

With the latest in optical technology, InFocus introduces the first short throw projector to its award winning and industry leading portable product line.

The XS1 delivers bright & brilliant images, with rich colors and high contrast for best in class picture quality. The digital & analog data/video inputs plus easy ceiling-mount capabilities make the wireless-compatible XS1 a simple choice for integration or tabletop use in business and education environments.



### Being close has its advantages.

- The short throw (0.7:1 ratio) reduces the distance of projector to screen to about one third of regular projectors.
- In ceiling mount mode, it eliminates the shadowing of the presenter when coming closer to the screen.
- In tabletop mode, it will allow you to move your projector from the center of the table to the very front. It will therefore be less obtrusive in a meeting.

### Complete interactivity and multimedia

The short throw feature enables the easy integration of the XS1 with interactive whiteboards and its broad analog and digital input range lets you connect any data or video source to the projector. In addition the on-board serial RS232 control makes it easy to integrate the XS1 into asset management systems.

### XS1 Overview

The XS1 has XGA native resolution (1024 x 768) which is the most common resolution for laptop and desktop computers. The XS1 puts out 2200 Max ANSI Lumens and a 1800:1 contrast Ratio which delivers bright The images with lush color saturation and

deep black levels, even in meeting spaces with ambient light. It utilizes the latest BrilliantColor™ technology to output true-to-life colors and shades through a short throw lens, providing big image flexibility to smaller rooms.

### Attention to details

- Long Lamp Life for a lower cost of ownership (4000 hours)
- Security: Kensington lock, User PIN, Removable Keypad (by removing the keypad the projector cannot be operated)
- Filter-Free Design & 24/7 compatible
- Digital Zoom - enables in-image zoom to highlight details during presentations
- Customizable Splashscreen (to display your company logo, school motto...)
- Presentation Timer to assist in tracking presentation time, meeting schedule or lesson time
- Quick Cooling mode to present and go
- Lamp Access on top & Second Serial Number Label on the back for an easy installation
- Solid warranties for a solid product: 2 years Projector & 6 months lamp warranty
- Advanced On Screen Display functions (All standard image and picture adjustments via on screen display (OSD) / Auto Search function, finding active sources automatically / 18 languages selectable for OSD)



#### Remote

The credit card type remote is small, functional and practical.



#### Wireless

The XS1 is 100% compatible with the InFocus LiteShow II wireless presentation adaptor, offering full featured wireless functionality of data, video and audio transmission to this versatile new projector.



## TECHNICAL SPECIFICATIONS\*

Native Resolution	• 1024 x 768 (XGA)
Display Technology	• 0.55" LVDS DLP® DMD w/ BrilliantColor™ from Texas Instruments™
Input Sources	• VGA (HD15), DVI-I, S-video, Composite Video, PC Audio (3.5mm), RS232, mini B type USB
Output Sources	• VGA (HD15), 12V trigger
Computer Compatibility	• VGA(640x480), SVGA(800x600), XGA(1024x768), SXGA(1280x1024), SXGA+(1400x1050)
Video Compatibility	• NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, SDTV(480i/576i), EDTV(480p/756p), HDTV(720p/1080i)
Brightness	• 2200 lumens
Contrast Ratio	• 1800:1
Number of Colors	• 16.7 million, True Color
Color Wheel	• 5 Segment (RGBYW)
Brightness Uniformity	• 80%
H-Synch Range	• 30~100kHz
V-Synch Range	• 50 ~87Hz
Dot Clock	• 13.5 MHz-140 MHz
Digital Keystone Correction	• +/- 25 deg.(vertical)
Standard Projection Lens	• F number: 2.42 • Focal length: 7.5 mm
Zoom	• Fixed
Throw Ratio	• 0.67:1 (distance to width)
Minimum Projection Distance	• 0.9 ~ 1.6 m
Lens Offset	• 120%
Aspect Ratio	• 4:3 (native) /16:9
Image Size (diagonal)	• 1.70m ~ 3.02m (67" ~ 119")
Projection Methods	• Front, Rear, Ceiling-front, Ceiling-rear
Audio	• 2.0W speaker (mono)
Control	• PC control through RS232
Lamp	• 200W / 3000 hours (Normal), 4000 hours (Eco)*
Security	• Kensington slot, PIN code, removable keypad
Product Dimensions	• 10.8" x 5.0" x 12.1" (WxHxD) 276 x 127 x 307 mm
Product Weight	• 4 kg / 8.75 lbs
Product Color	• Black
Power Consumption	• 285W +/-10% @ 110Vac
Power Supply	• 100~240Vac, 50/60Hz
Operating Temperature	• 5 - 35 °C / 41 - 35 F
Menu Languages	• English, French, German, Italian, Spanish, Portuguese, Swedish, Simplified Chinese, Traditional Chinese, Russian, Korean, Japanese, Dutch, Thai, Arabic, Czech, Polish, Turkish
Audible Noise	• 30dB(A)
Approvals	• UL/cUL, FCC, CE, CCC, PSB, MIC, EK, GOST
Product Warranty	• 2 year parts and labor
Lamp Warranty	• 6 Months

\* Actual lamp life may vary based on the ambient environment. Conditions affecting lamp life include temperature, altitude or rapidly switching the projector on and off.

+ InFocus reserves the right to alter product offerings and specifications at any time without notice.

## SHIPS STANDARD WITH:

- Wireless Remote Control (including batteries)
- Computer Cable
- Power Cord
- User Guide (Multi Language CD)
- Quick Start, Safety, Warranty & Registration Cards (printed)

## OPTIONAL ACCESSORIES

- Ceiling Mount, Wall arm
- Projection Screens
- Performance Cables & Adaptors
- InFocus LiteShow II Wireless Adaptor
- Carrying Cases

## LONG TERM CUSTOMER CARE

If you're happy, InFocus is happy. That's why every InFocus XS1 projector come with a standard 2-year limited factory warranty (including parts and labor) and a 6 month limited lamp-replacement warranty. Extended product & lamp warranty programs are also available.

For more information about warranty and service programs in your region, please visit:

[www.infocus.com/service](http://www.infocus.com/service)



**InFocus**  
The Big Picture

[www.InFocus.com](http://www.InFocus.com)

**InFocus Corporate Headquarters:** 27500 SW Parkway Avenue  
Wilsonville, Oregon 97070-9215, USA • Phone: (1) 503-685-8888  
(1) 800-294-6400 • Fax: (1) 503-685-8887

**In Europe:** InFocus International BV • Louis Armstrongweg 110 • 1311 RL Almere  
The Netherlands • Phone: (31) 20 5792000 • Fax: (31) 36 5392999  
Freephone: 008000 4636287 (008000 INFOCUS)

**In Asia:** 19 Tanglin Road • 7<sup>th</sup> Floor  
Singapore 247909 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525