


PG-F312X









Note: The PG-F312X is identical in appearance to the PG-F212X and the PG-F262X with the exception of the model number indication.

Dimensions (PG-F312X / F262X / F212X)



Optional Accessories

Lamp	USB Remote Receiver	Cable	Ceiling Mounts
 AN-F212LP	 AN-MR2	 AN-C3CP2 3-RCA to 15-pin D-sub cable (10' (3 m))	 AN-TK201 For high ceiling installation  AN-TK202 For standard ceiling installation  AN-60KT Installation adaptor

Note: Some of the optional accessories may not be available depending on the region. Please check with your nearest Sharp Authorized Projector Dealer or Service Center.

Specifications

Models	PG-F312X	PG-F262X	PG-F212X
Display device		0.55" DLP® chip x 1	
Resolution		XGA (1,024 x 768)	
Brightness	3,000 ANSI lumens	2,600 ANSI lumens	2,300 ANSI lumens
Contrast ratio		2,200:1	
Lens	F number	F2.5-2.6	
	Zoom	Manual, x1.15 (f=20.4 – 23.5 mm)	
	Focus	Manual	
Picture size	40" (102 cm) to 300" (762 cm)		
Projection distance	40":1.5 – 1.7 m, 100":3.7 – 4.3 m, 300":11.2 m		
Input signals	Computer RGB	UXGA**1*, SXGA+**2, SXGA*, WXGA*, XGA, SVGA, VGA	
	* Compression	Mac 21**1*, 19**2, 16**2, 13**2	
	DTV	1080P, 1080i, 720P, 576P, 576i, 540P, 480P, 480i NTSC, PAL, SECAM	
Input terminals	DVI-I (Compatible with HDCP)	x1	
	Computer / Component (mini D-sub 15 pin)	x1	
	S-Video (mini DIN 4pin)	x1	
	Video (RCA)	x1	
	Audio (ø3.5 mm stereo minijack)	x1	
	Audio (RCA)	x1 (L/R)	
Output terminals	Computer / Component (mini D-sub 15 pin)	x1	
	Audio (ø3.5 mm stereo minijack)	x1 (variable audio output)	
Control and communication terminals	USB (Type B)	x1	
	RS-232C (mini DIN 9 pin)	x1	
Horizontal frequency	15 – 110 kHz		
Vertical frequency	45 – 85 Hz		
Speaker	2 W (mono)		
Fan noise	37 dB (Bright), 29 dB (Eco+Quiet)	35 dB (Bright), 29 dB (Eco+Quiet)	32 dB (Bright), 29 dB (Eco+Quiet)
Projection lamp	250 W	230 W	200 W
Lamp life	4,000 hours (Eco+Quiet)		
On-screen display languages	English, German, Spanish, Dutch, French, Italian, Swedish, Portuguese, Russian, Polish, Hungarian, Turkish, Arabic, Persian, Simplified Chinese, Korean, Japanese		
Rated voltage	AC 100-240 V		
Rated frequency	50/60 Hz		
Input current	3.4 A	3.2 A	2.9 A
Power consumption (standby)	326 W (5.0 W) with AC 100 V, 316 W (5.7 W) with AC 240 V	303 W (5.0 W) with AC 100 V, 293 W (5.7 W) with AC 240 V	267 W (5.0 W) with AC 100 V, 259 W (5.7 W) with AC 240 V
Heat dissipation	1,230 BTU / hour with AC 110 V (Bright), 830 BTU / hour with AC 110 V (Eco+Quiet) 1,190 BTU / hour with AC 240 V, 810 BTU / hour with AC 240 V (Eco+Quiet)	1,140 BTU / hour with AC 110 V (Bright), 830 BTU / hour with AC 110 V (Eco+Quiet) 1,100 BTU / hour with AC 240 V, 810 BTU / hour with AC 240 V (Eco+Quiet)	1,010 BTU / hour with AC 100 V (Bright), 830 BTU / hour with AC 100 V (Eco+Quiet) 980 BTU / hour with AC 240 V, 810 BTU / hour with AC 240 V (Eco+Quiet)
Operation temperature	41°F to 95°F (+5°C to +35°C)		
Cabinet	Plastic		
Dimensions (main body only) W x H x D	10 41/64" x 3 33/64" x 10 7/16" (270 x 89 x 265 mm)		
Weight (approx.)	6.4 lbs. (2.9 kg)		
Supplied accessories	Remote control, two R-6 batteries, power cord (6' (1.8 m)), RGB cable (10' (3.0 m)), lens cap, DIN-D-sub RS-232C adaptor (5 57/64" (15 cm)), storage case, operation manual, CD-ROM		

Design and specifications are current as of March 2008, but are subject to change without notice.
 * Compatible in intelligent compression ** Analog RGB signal only
 • DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments.
 • All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers. Sharp makes no warranties or representations of any kind with respect to these products.
 • The lamp life may vary depending on the usage condition.

SHARP

PG-F312X/F262X/F212X
True XGA Data Projectors



PG-F312X

Sharp's New High-Performance DLP® Projectors with Vibrant Colour Reproduction from BrilliantColor™ Technology Provide Great Support for Business and School Applications




DLP® Performance with BrilliantColor™ Technology and Six-Segment Colour Wheel Providing Superior Reproduction of High-Resolution Fine Colour Nuances and High-Contrast Vivid Colours

Cutting Edge Technology Provides High-Quality Picture

BrilliantColor™ Technology with Six-Segment Colour Wheel

BrilliantColor™ Technology improves picture brilliance particularly for intermediate colours, providing natural, detailed images. Sharp has also developed a 3x Speed Colour Wheel with six colour segments including yellow and cyan added to red, green, blue, and white. 3x Speed Colour With Sharp's unique colour matching technology and these six colour combinations, images can be reproduced with highly realistic colours.



2200:1 High-Contrast, High-Quality Image

By utilizing the DLP® optical system and Sharp's optical technology, the projectors produce crisp details and sharper blacks in black parts thanks to a 2200:1 high contrast ratio.

Comparison of Dark Scenes



Comparison of Text and Graphics



PG-F312X Models in the same class as these generally provide a contrast ratio of 400:1.


DVI Terminal with DLP® System for Full Digital Projection

Full digital projection with the DVI input terminal and DLP® system enables virtually noise-free images from digital sources. The terminal also complies with High-bandwidth Digital Content Protection (HDCP) to support digital video content in high-definition.

DLP® Digital Image

Using DLP® chip, each pixel is individually composed of one of over a half a million micromirrors to produce a high resolution, and the micromirrors lie at a distance of merely one micron, providing a seamless finely detailed picture. Also, high-speed on/off switching delivers smooth moving scenes.

High-Resolution Seamless Image Comparison



3x Speed Colour Wheel

The projectors employ a colour wheel with an engine speed of up to 3x, improving colour break-up to an invisible level. Also, the non-contact Fluid Dynamic Bearings for the high-speed rotating colour wheel axle have a longer lifespan.

IP Conversion Image Processing


Image Processing provides optimal video performance. The motion-adaptive scan images produce smooth moving scenes and ensure smooth natural lines and edges for 480i and 576i.



Long-Life High-Performance DLP® Picture

With DLP® technology minimally absorbing high-output light, the projectors maintain uniform colour reproduction capability for a long period of time. Also, DLP® chip formation with finely structured mirrors provides stable performance and delivers high-quality pictures for longer periods. The DLP® chip contributes to a long lifespan.

In addition, because there is no burn-in or remaining afterimage, the projectors are ideal for still picture projection such as for guidance board applications and projecting CAD images.



* By RIT/Munsell Colour Science Laboratory Test

Outstanding Performance and High-Quality Reliability

High Brightness: 3000 ANSI lumens (PG-F312X), 2600 ANSI lumens (PG-F262X), 2300 ANSI lumens (PG-F212X)
Sharp's advanced optoelectronics technology maximizes light output, providing crystal clear images in amazingly high brightness.

Low Fan Noise

The DLP® high-speed colour wheel with non-contact Fluid Dynamic Bearings together with multiple ultra-quiet cooling fans reduce unpleasant noise, enabling quiet operation at 29dB in Quiet mode. The operation is so quiet it causes no disturbance even in meetings or school classes.


Filter-Free Design

The DLP® sealed system prevents dust, dirt and smoke from entering core parts of the optics to a much greater degree. The system also needs no filter and less maintenance, resulting in lower cost of ownership and longer use.

Intuitive Design and Functions to Support Presentation Convenience

Front Exhaust Engine

The new projector series has an exhaust engine on the front so that the viewers can remain focused on the screen without distractions of noise and air which may disturb viewers.



Direct Power Off Switching


Direct Power Off lets users immediately unplug the projector and take it from the location. In addition, it also helps control the power simultaneously for multiple projectors by using the room's primary power switch with the auto restart function.

Quick Start

It takes only approx. 3 seconds to project the image.

Setup Guide for Interactive Operation


The Setup Guide provides intuitive OSD images to show the next step interactively for setup including focus, zoom and height adjustment.



Setup guide is displayed after the projector is turned on.

Interactive Help Menu

The Help Menu displays any problems and assists the user in solving problems with operation.



Presentation Assist Remote Control

A variety of functions can all be performed with the projector remote control to aid your presentations including mouse control and page up and down. In addition, the following functions have been added for further performance.

Pointers: Five pointer icon shapes can be used to impressively draw attention to your subject.


Spotlights: Three spotlight sizes, ranging from 1/25 to 1/9 or 1/8 the screen, provide visual effects to focus on the specified subject.



Pointer icons



Spotlights



One-touch Advanced Picture Mode

Quickly and directly choose the appropriate settings for the picture mode and lamp brightness to match the intended application.

Multiple Connections for a Wide Range of Applications

Multiple Input Terminals


Projectors can be connected to DVD players, cable or satellite boxes, laptop and desktop computers, HDTV tuners, VCRs and video game consoles. DVI-I and D-sub terminals (in/out) are also provided.



Other Outstanding Features

- **Condenser Lens Optics**
Crisp detail, sharper black and ghost-less image.
- **4:3 and 16:9 Aspect Ratios and HDTV/DTV and DVD Compatible**
(1080P, 1080i, 720P, 576P, 576i, 540P, 480P and 480i).
- **Image Shift Function**
Images projected in 16 x 9 format can be vertically shifted for better viewing in limited spaces.
- **Theft Deterrent Function "System Lock"**
- **Key Lock Function**

Correlation of the Projector to the screen



Screen Size and Projection Distance

Picture size			Projection distance [L]		Distance from the bottom of the image to the lens centre [H]
Diag.	Width (cm)	Height (cm)	Minimum	Maximum	
300"	240" (610)	180" (457)	36'10" (11.2m)	—	7'9/16" (19cm)
200"	160" (406)	120" (305)	24'7" (7.5m)	28'4" (8.6m)	5'3/64" (13cm)
120"	96" (244)	72" (183)	14'9" (4.5m)	17'0" (5.2m)	3'1/32" (8cm)
100"	80" (203)	60" (152)	12'3" (3.7m)	14'2" (4.3m)	2'33/64" (6cm)
80"	64" (163)	48" (122)	9'10" (3.0m)	11'4" (3.5m)	2'1/64" (5cm)
40"	32" (81)	24" (61)	4'11" (1.5m)	5'8" (1.7m)	1'1/64" (3cm)

STRETCH Mode (16:9)

Picture size			Projection distance [L]		Distance from the bottom of the image to the lens centre [H]	Adjustable range of image position [S]
Diag.	Width (cm)	Height (cm)	Minimum	Maximum		
250"	218" (553)	123" (311)	33'6" (10.2m)	38'8" (11.8m)	27'19/64" (69cm)	±20'27/64" (±42cm)
200"	174" (443)	98" (249)	26'9" (8.2m)	30'11" (9.4m)	21'53/64" (55cm)	±16'11/32" (±42cm)
120"	105" (266)	59" (149)	16'1" (4.9m)	18'7" (5.7m)	13'3/32" (33cm)	±9'13/16" (±25cm)
100"	87" (221)	49" (125)	13'5" (4.1m)	15'5" (4.7m)	10'59/64" (28cm)	±8'11/64" (±21cm)
80"	70" (177)	39" (100)	10'9" (3.3m)	12'4" (3.8m)	8'47/64" (22cm)	±6'11/32" (±17cm)
40"	35" (89)	20" (50)	5'4" (1.6m)	6'2" (1.9m)	4'23/64" (11cm)	±3'11/64" (±8cm)

* Allow a margin of error in the above values.