

# SE2U

D L P™ P R O J E C T O R



HIGH QUALITY  
AT A LOW COST

BUSINESS APPLICATION VERSATILITY

 **MITSUBISHI  
ELECTRIC**  
PRESENTATION PRODUCTS  
**REVOLUTIONIZING COLOR™**

1500 ANSI LUMENS  
VERTICAL DIGITAL  
KEYSTONE ADJUSTMENT  
2000:1 CONTRAST  
RATIO  
SVGA 800 x 600  
HDTV-READY  
UP TO 2500-HOURS  
LAMP LIFE

The SE2U from Mitsubishi Digital Electronics is a full-featured projector at a discount price. Incorporating Mitsubishi's color depth and richness, the SE2U projector also combines high brightness and contrast ratio, long lamp life, and a lightweight form factor which provides a perfect solution for those looking for proven Mitsubishi Digital Electronics quality at an exceptionally affordable price.

- Lightweight form factor for easy portability
- Accepts computer input and signals from VCRs or DVD players
- 1500 ANSI lumens providing enough brightness for most office, classroom and conference room conditions
- 2000:1 contrast ratio for exceptional color depth and clarity
- Two-year parts and labor warranty and 90-day warranty on the lamp (both warranties available in U.S. and Canada), toll-free technical support, plus two-year Express Replacement Assistance (ERA) program that guarantees free replacement product shipped overnight for next business day delivery when and where available



### APPLICATION VERSATILITY

Although exceptionally portable, the SE2U supports front, rear and even ceiling installations. So no matter how unique your application is, the SE1U is a perfect match and will deliver dynamic images guaranteed to dazzle any size audience.

### PLUG AND PROJECT SIMPLICITY


Relax. With the SE2U, Mitsubishi has taken the worry out of your next presentation. In fact, the user-friendly SE2U is so easy and reliable to operate, you can focus your undivided attention on the audience, not the projector. Plug it in and start the show. It's that simple!

### VERTICAL DIGITAL KEYSTONE CORRECTION

Absolutely essential for portable projectors, Digital Keystone Correction reduces image distortion by allowing for vertical correction to create a more natural-looking picture even when it is difficult to set up the unit perfectly perpendicular with the screen. This important feature allows you to project at an angle without worrying about trapezoid image distortion or zigzagging.




Vertical distortion



No distortion

### INPUT AND OUTPUT TERMINALS




1. RGB Monitor Output
2. IR Sensor
3. Audio Input
4. USB Connector
5. S Video Input
6. RGB Input
7. Composite Video Input
8. Power Jack With Ground Terminal

### SPECIFICATIONS

Display Technology	0.55" single DLP™ chip with 12" DDR DMD™
Native Resolution	SVGA 800 x 600
Max. Resolution (compressed)	1024 x 768 and 1280 x 1024
Brightness	1500 ANSI Lumens
Contrast Ratio	2000:1 (full-on, full-off)
Lens Throw Ratio	1.6 ~ 2.0
Projection Lens	F = 2.6 ~ 3.1 100" @ 3.3m (wide)
Zoom/Focus Adjustment	Manual zoom and manual focus lens
Picture Size (4:3 aspect ratio)	45" ~ 180" diagonal
User Replaceable Lamp*	200 W lamp/2000-hour lamp life (normal mode) 160 W lamp/2500-hour lamp life (low mode)
Computer Compatibility	VGA ~ SXGA 640 x 400 ~ 800 x 600, compressed 1280 x 1024, Sync on green available
Video Compatibility	NTSC/NTSC 4.43/PAL (including PAL-M, NJ)/SECAM/PAL-60/DVD (component) 480P (525i, 525P) HDTV-ready (1080i, 720p)
Input Terminals	RGB: mini D-sub 15 pin x 1; Video: RCA x 1 = S video x 1
Output Terminals	RGB: mini D-sub 15 x 1
Communication Terminals	B-type USB terminal for mouse port (page up and down only)
Audio Speaker	Mono 1W
Scanning Frequency	Horizontal: 24 - 81 kHz, Vertical: 48 - 85 Hz
Remote Control	Wireless, card type, full projector control; Powerpoint page up/down via USB
Power Consumption	285 W
Dimensions (W x H x D)	11.14 x 4.21 x 9.0" (283 x 107 x 229 mm)
Weight	6.4 lbs (2.9 kg)
Power Supply	AC 100 ~ 240V / ±10%, 60/60 Hz
Safety Approvals	CSA, CSA NRT L/C, FCC Class-B
Warranty	Two-year parts and labor warranty and 90 day warranty on lamp (both warranties available in U.S. and Canada). Also includes two-year Express Replacement Assistance program that guarantees free replacement projector shipped overnight for next business day delivery when and where available
Accessories	Standard: Soft carrying case; AC power cable; d-sub RGB cable; RS-232C cable; AV cable; USB cable; S-video cable; remote control with battery; mouse adapter; lens cap; user manual CD; quick reference card Optional: Spare lamp (VLT-SE2LP)
Special Features	Vertical digital keystone correction ±7°; 8 language OSD; auto input source search

For more information on the SE2U or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Detailed technical specifications available upon request.



Diagonal (inch)	Screen Size		Projection Distance (L)/(approximate)	
	Width (inch)	Height (inch)	(max. inch)	(min. inch)
45	36	27	57.6	72.0
60	48	36	76.8	96.0
80	64	48	102.4	128.0
100	80	60	128.0	160.0
150	120	90	192.0	240.0
180	144	108	230.1	288.0

The above numbers are approximate, and may be slightly different from the actual measurements.

To find the approximate distance between the projector and screen: Multiply the width of the screen x 1.6 maximum, 2.0 minimum.

©2004 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. Digital Light Processing, DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments, Inc. All other trademarks or registered trademarks are the property of their respective holders. \*The projector lamp contains mercury. Please dispose of properly.



Printed on 50% recycled paper including 20% post-consumer fibers.

**Mitsubishi Digital Electronics America, Inc.**  
Presentation Products Division  
9351 Jeronimo Road  
Irvine, CA 92618  
Toll Free: 888-307-0349  
email: ppdinfo@mdea.com

**Technical Support:**  
Toll Free: 888-307-0309  
Email: tsupport@mdea.com

**Canada:**  
Mitsubishi Electric Sales Canada Inc.  
Information Technologies Group  
Markham, Ontario  
905-475-7728  
www.MitsubishiElectric.ca