

TOSHIBA

Leading Innovation >>>

| x150



> **MINIMUM
WEIGHT**

> **MAXIMUM
COLOURS**

> **MOBILE
PRESENTATION**

- High security by password-function
- Weight 1.8 kg
- NCE 5™-Chip



LCD stands for Liquid Cristal Displays
NCE 5™: Colour optimization by Toshiba



| | |
|-----------------------------|--|
| Display | 0.63" LCD Chip |
| Resolution | XGA 1,024 x 768 |
| Brightness | 2,600 ANSI-lumens |
| Colour reproduction | 16.7 mio. colours |
| Contrast | 600:1 |
| Projection format | 4:3 switchable to 16:9 |
| Lamp | 180 W (TLPLW21) |
| Max. lamp life | up to max. 2,000 hours/ up to max. 3,000 hours in ECO mode |
| Lens | F = 1.7 - 1.87 / f = 19.2- 23.1 mm, manuell focus and zoom |
| Zoom | 1.2 x |
| Frequency (hor./vert.) | 15 - 106 kHz / 50 - 85 Hz |
| Projection | front, rear and ceiling |
| Digital keystone correction | full auto keystone vertical +/- 45° |
| Picture size (diagonal) | 0.7 - 7.7 m |
| Projection offset | 71 % |
| Input signals | NTSC / PAL / SECAM, 480i, 480p, 576i, 576p, 720p, 1,080i, 1,080p, VGA, SVGA, XGA, WXGA, SXGA, UXGA (compr.) |
| Inputs | 2 x RGB, audio, video (1 x RCA), S-video, USB |
| Outputs | 1 x RGB switchable in/out, audio |
| Serial interface | RS-232C (D-sub 9pin) |
| Power supply | AC 100 - 240 V, 50/60 Hz |
| Loudspeaker | 1 W mono |
| Dimensions (W x H x D) | 268 x 70 x 189 mm |
| Weight | 1.8 kg |
| Operation noise | ECO Mode 28 dB / normal 32 dB |
| Specials | auto keystone correction, instant shut down, user logo capture, NCE 5™, password, USB memory reader |
| Accessories | remote control with laserpointer and batteries, mouse remote receiver, softcase, owners manual (CD-ROM), RGB- and power-cable |
| Options | ceiling mount, spare lamp, camera c001, RJ45 control adapter |
| Menu guidance | 25 languages: English, French, German, Italian, Spanish, Portuguese, Russian, Swedish, Turkish, Polish, Japan- ese, Chinese (simple/traditional), Korean, Indonesian, Danish, Czech, Hungarian, Dutch, Finnish, Norwegian, Greek, Rumanian, Thai, Arabic |

