



PLC-XW65

- Easy-to-carry projector with a net weight of only 1.6 kg
- 2,500 ANSI lumens and XGA resolution provide a bright and detail-oriented projection
- Wide angle lens with 1,2 optical zoom allows flexible positioning (1.33–1.62 : 1)
- Automatic set-up (source recognition, keystone-correction and PC-adaption) enables operation within seconds
- Anti-theft function through PIN code lock, Key lock
- Direct Power On/Off allows switching the projector on/off without delay
- 3 years warranty, 1 year lamp warranty

PLC-XW65

TECHNICAL DATA	PLC-XW65
Category	Business & Education
Panel	3 x 0.63" TFT p-Si (4 : 3), micro lens
Projection Lamp	175 W UHP (LMP-129)
Brightness in ANSI lumens	2,500
Lamp Life	3,500 h (eco mode)/2,000 h (normal mode)
Fan Noise	30.9 dB (eco mode)/34.6 dB (normal mode)
Standard Lens	F = 1.77–1.99/f = 17.4–21.1 mm*
Throw Distance Ratio	1.33–1.62 : 1*
Throw Distance	1.1–10.0 m*
Contrast Ratio	600 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min.–max. (diagonal)	40"–300"
Uniformity	85 %
Bandwidth/Frequency	140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PALM/N
Connections	Input 1: D-Sub15 (RGB/Component/S-Video) Input 2: D-Sub15 (RGB) or monitor out Input 3: RCA (Composite) Audio: 3.5 mm Stereo Jack, 2 x RCA (R/L mono) Audio output: 3.5 mm Stereo Jack Control input Jack: Mini DIN 8-pin (RS232)
Audio Function	1 W Mono
Keystone Correction	vertical +/-20°
Up/Down-Ratio	6 : 1 (Fixed U/D Ratio)
HDTV Compatibility	480i/480p/575i/575p/720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	1.2 x/manual focusing
Power Consumption/Voltage	185 W (eco mode)/225 W (normal mode)/4 W (stand-by mode)/100–240 V
Warranty	3 years, 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	265.0 x 76.1 x 189.0 mm
Weight	1.6 kg
Standard Accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Carrier bag, Lens cover with fastener and cord
Optional Accessories	SCART/D-Sub 15 cable (POA-CA-SCART), Remote control with laser pointer (POA-RCKIT03), Components/D-Sub15 cable (POA-CA-COMPVGA), Presentation kit including mouse function (POA-RCKIT04), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40–70 cm (POA-CM02), Ceiling mount 70–110 cm (POA-CM03)
Lenses	Standard Lens

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 09/2008

