

Show your **ability**
with perfect presentation!

 **LG**
www.lge.com

LG DATA PROJECTOR SERIES
DS125 | DX125 | DX130


Materialization of the smallest,
highest brightness!



 **LG**
Life's Good

LG Data Projector

For the greater value than success, have an ambitious dream!



PROFESSIONAL PROJECTOR

It presents perfect presentation with excellent brightness and astounding mobility



DS125

PROFESSIONAL USE

- MAIN SPEC**
- 0.55" 12Deg. DLP DDP 2000
 - Native SVGA(800x600)
 - 2500 ANSI Lumens
 - Ultra Light Weight 1.9kg
 - Contrast 2000:1
- FEATURES**
- 3 Level Brightness Mode
 - DVI, Composite, Component, S-Video, USB
 - HD Compatible
 - Magnesium alloy cabinet
 - Carry Case
 - 1W Mono speaker

DX125

PROFESSIONAL USE

- MAIN SPEC**
- 0.55" 12Deg. DLP DDP 2000
 - Native XGA(1024x768)
 - 2500 ANSI Lumens
 - Ultra Light Weight 1.9kg
 - Contrast 2000:1
- FEATURES**
- 3 Level Brightness Mode
 - DVI, Composite, Component, S-Video, USB
 - HD Ready
 - Magnesium alloy cabinet
 - Carry Case
 - 1W Mono speaker

DX130

PROFESSIONAL USE

- MAIN SPEC**
- 0.7" 12Deg. DLP DDP 2000
 - Native XGA(1024x768)
 - 3000 ANSI Lumens
 - Ultra Light Weight 1.9kg
 - Contrast 2000:1
- FEATURES**
- 3 Level Brightness Mode
 - DVI, Composite, Component, S-Video, USB
 - HD Ready
 - Magnesium alloy cabinet
 - Carry Case
 - 1W Mono speaker

SPECIFICATION

Benefit from the value that lies beyond success through secure and detailed presentation

LG DATA PROJECTOR

General Specification

| | DS125 | DX125 | DX130 |
|-------------------------------------|--|--|--|
| Projection System | DLP™ (0.55" DMD) | DLP™ (0.55" DMD) | DLP™ (0.7" DMD) |
| Resolution | 800x600 (SVGA) SXGA+(1400x1050) | 1024x768 (XGA) SXGA+(1400x1050) | 1024x768 (XGA) SXGA+(1400x1050) |
| Aspect Ratio Correction | Native 4:3, Support 16:9 | Native 4:3, Support 16:9 | Native 4:3, Support 16:9 |
| Brightness | 2500 | 2500 | 3000 |
| Contrast Ratio (FOFO) | 2000:1 | 2000:1 | 2000:1 |
| Uniformity(min) | 85% | 85% | 85% |
| Noise | Normal / Silent | 32dB / 30dB | 32dB / 30dB |
| Color wheel | 4 Segment(R/G/B/W) | 4 Segment(R/G/B/W) | 4 Segment(R/G/B/W) |
| Projection Lens | Focal Length Zoom Style Screen Size | 22mm(wide) - 25.5mm(Tele) manual (x 1.16) | 22mm(wide) - 25.5mm(Tele) manual (x 1.16) |
| Projection Image | 30" - 300" | 30" - 300" | 30" - 300" |
| Lamp Type | 200W | 200W | 200W |
| Lamp Life | 3000 hr 4000 hr | 3000 hr 4000 hr | 3000 hr 4000 hr |
| Dimension (mm) | 260mm x 205mm x 69mm | 260mm x 205mm x 69mm | 260mm x 205mm x 69mm |
| Weight | 1.9Kg | 1.9Kg | 1.9Kg |
| Video Compatibility | NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N | NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N | NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N |
| HD Ready | 1080i / 720p / 576P / 576i / 480p / 480i | 1080i / 720p / 576P / 576i / 480p / 480i | 1080i / 720p / 576P / 576i / 480p / 480i |
| OSD Language | Korean / English / French / Spanish / German / Portuguese / Swedish / Russian / Japan / Italian / Chinese Simplified / Chinese Traditional | Korean / English / French / Spanish / German / Portuguese / Swedish / Russian / Japan / Italian / Chinese Simplified / Chinese Traditional | Korean / English / French / Spanish / German / Portuguese / Swedish / Russian / Japan / Italian / Chinese Simplified / Chinese Traditional |
| Power Consumption | 255W | 255W | 255W |
| Power Supply | AC 90 - 264V(Free Voltage), 50Hz/60Hz | AC 90 - 264V(Free Voltage), 50Hz/60Hz | AC 90 - 264V(Free Voltage), 50Hz/60Hz |
| Sound | 1W Mono | 1W Mono | 1W Mono |
| Conformances (Regulation) | CE, CB, GÖST, MIC, SABS | CE, CB, GÖST, MIC, SABS | CE, CB, GÖST, MIC, SABS |
| INPUT/OUTPUT Terminals | | | |
| PC | PC Input (D-sub 15pin) PC Sound in USB | 0 (DVI to D-Sub) 1 0 (Flash upgrade) | 0 (DVI to D-Sub) 1 0 (Flash upgrade) |
| A/V | S-Video Component Composite Digital input IR Port Sound L/R | Yes, thru DVI-I Composite Video (RCA x 1) DVI- HDCP 0 1 w mono speaker | Yes, thru DVI-I Composite Video (RCA x 1) DVI- HDCP 0 1 w mono speaker |
| Functions | | | |
| Digital Keystone Correction | 0(Vertical) 15' | 0(Vertical) 15' | 0(Vertical) 15' |
| IR Remote Control | 0 | 0 | 0 |
| Freeze | 0 | 0 | 0 |
| Mute | 0 | 0 | 0 |
| ARC(aspect ratio correction) | 0 | 0 | 0 |
| Plug & Play | 0 | 0 | 0 |
| Auto Tracking | 0 | 0 | 0 |
| Logo Back | 0 | 0 | 0 |
| Flip Vertical | 0 | 0 | 0 |
| Flip Horizontal | 0 | 0 | 0 |
| DVI with HDCP | 0 | 0 | 0 |
| White enhance(white peaking) | 0 | 0 | 0 |
| Gamma Correction | 0 | 0 | 0 |
| Lamp | AL-JDT1 | AL-JDT1 | AL-JDT2 |