

The Perfect Experience / —

Full HD D-ILA front projector with 50,000:1 native contrast ratio, three D-ILA devices, 2x motorised zoom lens with motorised focus, Clear Motion Drive, Inverse telecine (reverse 2-3 pulldown), Certified by ISF, Certified by THX, JVC's original picture modes, Screen Adjustment Mode, flexible set-up and more



3x 0.7"-os Full HD-s D-ILA chippek Bemeneti jel fogadó képesség: 1080p Valós FULL DHD felbontás 1920x1080 200W UHP (ultra high-pressure mercury) lamp (lamp life: approx. 3000 hours in Normal mode) Vetítési méret:60" tól 200"-ig Vetítési távolság: 3.01m től 6.08m-ig (100") Terminals: RS232C x 1, HDMI x 2 (v.1.3), Component x 1, S-Video x 1, Composite x 1, PC x 1, Trigger x 1

Some of industry's highest 50,000:1 native contrast ratio\* realised by the combination of enhanced full HD D-ILA devices and optical engine

Nagyteljesítményű 2x zoom lencse motorizált fókusszal, széles átmérőjű, 17 elemből álló lencse rendszerrel,( 15 csoportban) 2 ED lencsével.

Clear Motion Drive technológia

Inverse telecine (reverse 2-3 pulldown)

Certified by ISF/Certified by THX

JVC's original picture modes

Screen Adjustment Mode

Vertikális széthúzás az anamorfikus lencsével együtt a vetített képek a vetítőlapon teljes kitöltését teszik lehetővé.

Quiet operation: only 19dB

Newly designed remote control

## Full HD D-ILA házimozi projektor

Television	DLA-HD950BE
<b>Kép</b>	
Device	0.7-inch D-ILA x3
Display device	Full HD D-ILA device
Resolution	1920 x 1080 pixels
<b>Lens</b>	
Zoom	2 x motorised zoom / focus
f	f=21.4mm - 42.8mm
F	F=3.2 - 4
Projection size	60 - 200 inches (screen diagonal)
Lens shift function	+/-80% Vertical and +/-34% Horizontal (motorised)
Light source lamp	200W UHP (lamp life: approx. 3,000 hours in Normal mode)
Brightness	900lm
Contrast Ratio	Native: 50,000:1
Video input signals	480i/p, 576i/p, 720p 60/50, 1080i 60/50, 1080p 60/50/24
<b>PC input signal</b>	
Digital	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, WSXGA+, WUXGA
Analogue	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+
<b>Video input terminals (back panel)</b>	
HDMI	2 (ver.1.3)
Component	1 (RCA)
S-Video	1 (mini DIN)
Composite	1 (RCA)
PC	1 (D-sub 15-pin)
<b>Control terminals</b>	
RS232C	1 (D-sub 9-pin)
Trigger	1 (mini jack)
<b>Általános</b>	
Noise level	19dB (in Normal mode)
Power requirement	AC 110V-240V, 50/60 Hz
Power consumption	310W (Stand-by: 0.7W)
Dimensions: W x H x D, mm	365 x 167 x 478
Weight, kg	11.2