

U4

PLUS

U4-SERIES



INTRODUCING THE BRIGHTEST PROJECTORS IN THEIR CLASS: THE 3 LB.

U4 SERIES FROM PLUS. WITH UP TO 2000 LUMENS AND A 2000:1

CONTRAST RATIO, THE U4 SERIES BOASTS IMAGERY THAT'S CRISPER,

CLEANER AND BRIGHTER THAN EVER. THE PORTABLE AND CEILING-

MOUNTABLE U4 ALSO COMES WITH AN ECO-MODE OPTION THAT LETS

YOU SAVE BULB LIFE. AND NOW THE U4 IS WIRELESS TOO!

Up to 2,000 ANSI lumens
corner-to-corner brightness

Only 3 pounds

Wireless state of the art projecting

Eco-mode lets you increase
lamp life by 30%

Digital zoom instantly targets and
enlarges the fine print at the touch of
a button

Connects to virtually any computer
or video source

Network Connectivity

Digital keystone correction

HDTV compatible

CompactFlash Memory Slot



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 800
BEAVERTON, OR 97005
866-427-8855 • 503-748-8700
www.plus-america.com

U4

U4-SERIES



PLUS

Specifications	U4-232	U4-237
Resolution	XGA, 1024 x 768 pixels	XGA, 1024 x 768 pixels
RGB Signal	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)
Brightness	1800 Lumens	2000 Lumens
Contrast Ratio	2000:1 (Full on/off)	2000:1 (Full on/off)
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9
Projection Lens	F=2.6-2.9 f=27.5-33mm 1:1.2 Manual Zoom Manual Focus	F=2.6-2.9 f=27.5-33mm 1:1.2 Manual Zoom Manual Focus
Digital Keystone Correction	+17/-22 degrees	+17/-22 degrees
Digital Zoom	2x	2x
Light Resource	180-watt lamp, 1,500 hrs. 2,000 hrs. in Eco-mode	180-watt lamp, 2,000 hrs. 3,000 hrs. in Eco-mode
Color Palette	16.7 million colors	16.7 million colors
Projection Positions	Front/rear, Table/ceiling	Front/rear, Table/ceiling
Projection Distance	3.9-38ft / 1.2-11.6 m	3.9-38ft / 1.2-11.6 m
Image Size	26"-300" diagonal	26"-300" diagonal
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 576p, 720p, 1080i)	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 576p, 720p, 1080i)
Audio	Mono 0.5 watt	Mono 0.5 watt
Dimensions Excluding Lens and Stand:		
Height	2.08 in./53 mm	2.08 in./53 mm
Width	7.5 in./190 mm	7.5 in./190 mm
Length	9.5 in./242 mm	9.5 in./242 mm
Weight	3.3 lb./1.5 kg	3.3 lb./1.5 kg
Included Accessories:		Optional Accessories:
<ul style="list-style-type: none"> ■ Wireless remote control ■ Power cable (6 ft./1.8 m) ■ Video cable (6.5 ft./2 m) ■ S-video cable (6.5 ft./2 m) ■ 3.5 mm mini plug audio cable (6.5 ft./2 m) ■ 3.5 mm stereo plug to RCA ■ DVI to mini D-sub 15 pin (6.5 ft./2 m) ■ Soft carrying case ■ User's manual ■ 802.11b Wi-Fi CompactFlash Card (U4-237) 		<ul style="list-style-type: none"> ■ ATA shipping cases ■ VGA cables (9-12 ft./2.7-3.6 m) ■ DVI-D cable (6.5ft/2 m) ■ 3.5mm, 4-pole plug to RCA component cable (5ft./1.5 m) ■ 15-pin to RCA component cable (10 ft./3 m) ■ Presenter-2-Go - laptop-free presentation system ■ Display-to-Go - output DVI from any laptop ■ Ceiling mount kit



Presentation Screens

Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.



Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



Remote Controls

Choose from a variety of wireless remotes to fit any presentation environment.



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 800
BEAVERTON, OR 97005
866-427-8855 • 503-748-8700
www.plus-america.com