IN2100 (SERIES)





Ease of Use - Maximum Functionality
Essential Features - Brilliant Image Quality

Optional Accessories

Cables & Adapters LiteShow II (INLITESHOW2) Replacement Lamp (SP-LAMP-057) Universal Ceiling Mount (SP-CEIL-UNIV) Extension Arms (SP-EXTARM-01, 02, 03, 04) Alternate Remote (HW-COMMANDER) Alternate Remote (HW-PRESENTER-RF-R) Long Haul USB (WH-DOUSB-EXTENDER)

For more information, please visit: www.infocus.com/Accessories.aspx

Warranty

Providing the highest quality products and support is very important to InFocus. The IN2100 series digital projectors come standard with a 5 year limited factory warranty (including parts¹ and labor²) a 6 month limited lamp replacement warranty and 5 year DLP warranty. Extended product and lamp warranty programs are also available.

For more information, please visit: www.infocus.com/Support/Warranty.aspx













IN2100 (SERIES) FEATURES

Dynamic Messaging System (DMS)

IN2114: LitePort USB IPEG Player

BrilliantColor **Closed Captioning**

Control Ready

Lens Cap Slider

Logo Capture

Dust Resistant Design

InFocus User Interface

LiteSwitch Instant On/Off

LiteShow II Wireless Ready LiteTouch Touchsense Keypad

Low Power Standby (<1 W) ProjectorNet Web Browser Sleep Timer



Bright Ideas Made Brilliant

www.infocus.com

INFOCUS CORPORATE HEADQUARTERS


13190 SW 68th Parkway Portland, Oregon 97223-8368, USA Phone: (1) 503-685-8888

> Toll Free: (1) 800-294-6400 Fax: (1) 503-685-7239

INTERNATIONAL HEADQUARTERS

1 Fullerton Road One Fullerton Singapore 049213 Phone: (65) 6513-9600 Fax: (65) 6238-0535

LitePort slideshow



	Native Resolution	IN2112 - SVGA 800 × 600 IN2114 - XGA 1024 × 768
	Maximum Resolution	WUXGA (1920 × 1200)
ı	Display Technology - DMD	DLP Technology .55" LVDS DDP2430 with BrilliantColor
ı	Brightness	3000 ANSI lm (2400 lm Eco Mode)
	Lamp Life**	4000 Hrs Eco Mode (3000 Hrs Normal)
	Contrast Ratio	2100:1 Typical
	Audible Noise	28 dB Eco Mode (32 dB High Power)
	Computer Compatibility	PC, MAC
	Keystone Correction	Manual, +/-30 degrees
	Number of Colors	16.7 Million, True Color
	Aspect Ratio	Native 4:3 (5:4, 16:9, 16:10 Supported)
	Lamp Power	185 W
	Power Supply	100 ~ 240 Vac, 50/60 Hz
	Zoom Ratio	1.2:1
	Throw Ratio	1.62 ~ 1.95
	Video Compatibility	NTSC / NTSC4.43 / PAL / PAL-M / PAL-N / SECAM SDTV: 480i, 576i
		EDTV: 480p, 576p
		HDTV: 720p, 1080i, 1080p
ŀ	Audio	10 W (2 × 5 W)
ı	Input Sources	2 × D-sub HD15, S-Video, Composite Video,
	,	2 × assignable audio in (3.5 mm),
		IN2114: LitePort
h	Projection Distance	3.94 ft ~ 32.8 ft / 1.2 m ~ 10 m
	Projection Methods	Front, Rear, Ceiling Front, Ceiling Rear
ı	Product Weight	7 lbs / 3.17 kg
	Product Dimensions - W×D×H	12.4 × 9.5 × 4.6 in / 315 × 241 × 117 mm
	Product Color	Black
	Shipping Dimension - W×D×H	8.8 × 18.8 × 13.1 in / 223 × 477 × 332 mm
	Shipping Weight	14.3 lbs / 6.48 kg
L	Maximum Altitude	10,000 ft / 3,000 m
	Remote Control	Navigator - 3
	Ships With - Accessories	Remote, VGA Cable, Power Cord, USB Cable, Carry Case,
		Safety Instructions, Projector User's Guide,
L		DisplayLink User's Guide
	Menu Languages	English, French, German, Italian, Korean, Norwegian,
		Portuguese, Russian, Spanish, Traditional Chinese,
		Simplified Chinese, Swedish, Finnish,
ŀ	. ((:1)6 . :	Danish, Dutch, Polish, Turkish
L	Lamp (particle) Containment	Tested to contain particles larger than 0.8 mm ***
l	Accessories Warranty	90 days
l	Approvals	C-Tick (Australia), NOM (Mexico), CE (Europe), cMETus (USA & Canada), FCC (USA), IRAM (Argentina),
l		GOST (Russia), MIC & eK (South Korea), CCC (China),
		PSB (Singapore)
l	Security	Kensington Lock
п		I NETISTIELUT LUCK

- * Product specifications, terms, and offerings are subject to change at any time without notice.
- ** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.
- *** Tested to contain particles larger than the specified size in any dimension

