

compact 225

GeHa

PRÄSENTATIONS-SYSTEME



On the way



Maximum screen size for daylight projection (recommended size in cm)



Maximum room size for daylight projection (recommended size in m²)

>> The travel companion

At only 1.1 kg, this is the lightest projector of the GEHA range. It comes with a quality carrier bag for easy transport.

>> Compact design - great performance

The light output of 2200 ANSI lumen is sufficient to provide a good picture under any lighting conditions.

>> High-contrast images

Whether you wish to show high-contrast business presentations of detailed video images – this model with a contrast ratio of 2200:1 offers you all you need.

>> Complete range of accessories

The device comes with all necessary cables, a remote control unit with laser pointer and an attractive carrier bag.

>> Ready for operation in seconds

Thanks to the quick cooling function, the projector is ready within seconds for the next presentation at a different location.

>> New: Digital Input

Now delivered with a digital HDMI input, that can be adopted to DVI.






Geha compact 225

Order no.	30 281 360
Display technology	0,55" DLP™
Resolution (physical)	XGA 1024 x 768 pixel, from VGA (640 x 480) to SXGA+ (1400 x 1050)
Brightness (norm./eco. mode) in ANSI-Lumen	2200/1700
Contrast ratio	2200:1
Weight in kg	1.1
Dimensions (W x D x H) in mm	206 x 156 x 64
Noise level (full/eco)	33/31 dB
Lens system	Zoom 1.1x man. f=22 to 24 mm/F=2.4 to 2.55
Projection distance	from 1.2 m to 12 m
Image size (diagonal)	from 0.78 m to 7.78 m
Throw ratio (distance to image width)	1.93 to 2.13 : 1
Offset	115 %
Keystone correction	vert. +/-18° manual
Functions	digital keystone correction, ceiling mount, rear projection, digital zoom, Freeze, Mask, OSD, Quick Start, Quick cool down, pass word protection
Lamp	165 Watt
Lamp life time (normal/economy mode)	Up to 3000 h/4000 h
Power supply	100 to 240V AC/ 50/60 Hz
Power consumption (on/stand-by)	225/<10 Watt
Video compatibility	PAL/SECAM/NTSC, 480i/p, 525i/p, 576i/p, 625i/p, 720p, 1080i
Horizontal frequency	15 to 100 kHz
Scanning rate	43 to 85 Hz
Bandwidth	110 MHz
Inputs	digital (1 x HDMI with HDCP (can be adopted to DVI)), RGB (1 x 15 pin D sub), Video (1 x RCA), S-Video (1 x Mini-DIN 4pin, -SCART (optional via adapter))
WLAN Specification	-
Outputs	-
RS232 port	-
LAN port	-
Mouse port	1 x USB Mini 5 pin
Sound system	-
Standard accessories	Projector, lens cap, power cable, VGA cable, USB cable, remote control with laser pointer, batteries, CD with manuals, soft case
Warranty	36 month
Lamp warranty	1 year or 1000 hours



Figures refer to image width x image height

All dimension in m; drawing not to scale



Accessories:

Order no. Specification

60 281 501	165 W lamp kit for compact 225, life time up to 4,000 h (economy mode)
------------	--