MOBILE PROJECTOR

NEC NP215

Brilliant color DLP projector for business and education - with long life lamp and excellent price/ performance ratio.

- Native Resolution: 1024 x 768 (XGA), 2500 ANSI lumens
- Brilliant Color and VIDI technology for excellent color reproduction
- Low operating cost and carbon savings meter
- 5000 hours Lamp Life (Eco Mode)
- Control and monitoring via network and RS-232

see more.
NEC Display Solutions

NEC NP215

TECHNICAL SPECIFICATIONS

Display	1 x 1.4 cm (0.55") DDR DMD Chip (Aspect Ratio 4:3)
Lamp	180 W DC
Lamp Life [hrs]	3500 (5000 Eco Mode)
Brightness [1]	2500 ANSI Lumens
Contrast Ratio [1]	2000:1
Diagonal: min. / max. [cm]	76 / 762
Projection Distance [m]	1.2 – 13
Projection Factor	1.95 – 2.15 : 1
Frequency	Horizontal: 15–100 kHz; Vertical: 50 – 120 Hz
Native Resolution	1024 x 768 (XGA)
Supported Resolutions	1920 x 1080; 1600 x 1200; 1400 x 1050; 1280 x 1024; 1280 x 960; 1280 x 720; 1024 x 768; 832 x 624; 800 x 600; 640 x 480
ComputerAnalog	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x 3.5 mm Stereo Mini Jack
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
Video Signals	PAL / PAL60 / NTSC / SECAM / NTSC 4.43 / PAL-N / PAL-M
Audio Functions [W]	1 x 7 (mono)
Zoom / Focus Adjustment	Manual / Manual
Benefits	6-segment Colour Wheel; Auto Power Start; Automatic and manual vertical Keystone Correction (V= ±40°); BrilliantColor™ and VIDI technology; Long Life Lamp; Off-Timer; Plug&Play; Quick-Start-/Quick-Power-Off Function
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; Keystone Correction; Lamp Mode Control; Magnify-function; Optional Presentation and Mouse Control; Picture Adjust; Picture Mode; Picture Mute; Source Select
Dimensions (W x H x D) [mm]	310 x 95 x 247 (without lens and feet)
Weight [kg]	2.5
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	233 max.; 210 Eco Mode; 0.7 Network Stand-by Mode
Fan Noise [dB (A)]	31 / 34 (Eco / Normal)
Safety and Ergonomics	CE; TÜV GS; RoHS; TCO
Warranty	Projector: 3 years pan-European Premium Service; Lamp: 6 Months, max. 1000 Hrs
Shipping Contents	Projector; IR Remote Control (RD-443E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap
Optional Accessories	Ceiling Mount Kit (NP11CM); Lamp (NP13LP); Mouse Receiver (NP01MR); Universal Ceiling Mounts (NP01/02/03/04/05UCM)

[1] Compliance with ISO21118-2005

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 11/09

www.nec-display-solutions.co.uk

NEC Display Solutions UK Ltd, 1 Victoria Road , W3 6BL London
Phone: +4420899-38111, Fax: -27161, e-mail: info@uk.neceur.com