ALLROUND INSTALLATION PROJECTOR

NEC NP2200

Installation projector with intense brightness, 5 optional bayonet lenses and lens shift.

- Native Resolution: 1024 x 768 (XGA)
- Brightness: 4200 ANSI Lumens
- Lens Shift (vertical and horizontal)
- Lens options

see more.
NEC Display Solutions

NEC NP2200

TECHNICAL SPECIFICATIONS

Display	3 x 2.03 cm (0.8") p-Si LCD Panel with MLA (Aspect Ratio 4:3)
Lamp	300 W (264 W Eco Mode)
Lamp Life [hrs]	2000 (3000 Eco Mode)
Brightness [1]	4200 ANSI Lumens (approx. 88% in Eco Mode)
Contrast Ratio [1]	600:1
Lens	F= 1.7–2.2, f= 24.4–32.5 mm
Diagonal: min. / max. [cm]	76 (30") / 1270 (500")
Projection Distance [m]	1.2 – 21.9
Projection Factor	1.5 – 2.0 : 1
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz or more); Vertical: 50 – 120 Hz
Native Resolution	1024 x 768 (XGA)
Supported Resolutions	1600 x 1200 (UXGA); 1400 x 1050 (SXGA+); 1280 x 1024 (SXGA); 1280 x 768 (WXGA) with Advanced AccuBlend™ Technology; 1280 x 720 (HDTV 720p); 1152 x 900 (SGI. SUN); 1152 x 870 (Mac); 1024 x 768 (XGA); 832 x 624 (Mac); 800 x 600 (SVGA); 768 x 576 (PAL 15.6 kHz); 720 x 576 (SDTV 557p); 720 x 480 (SDTV 480p); 640 x 480 (NTSC 15.7 kHz); 640 x 480 (VGA/Mac)
ComputerAnalog	Input: 1 x 5BNC, shared with Component Signal (YPbPr); Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
Computer Digital	Input: 1 x DVI-D (with HDCP)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x RCA Stereo for Video and S-Video; Input: 2 x 3.5 mm Stereo Mini Jack for Computer analog and digital; Output: 1 x 3.5 mm Stereo Mini Jack (variable) for Computer 1, 2, 3 (DVI-D), Video or S-Video
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
Video Signals	PAL / PAL60 / NTSC / SECAM / NTSC 4.43 / PAL-N / PAL-M
Audio Functions [W]	2 x 5 (stereo)
Zoom / Focus Adjustment	Manual / Manual
Benefits	3 x Security System; Auto Color Correction; Auto Power-ON Function; Carbon Savings Meter; Help Function; IR Remote Control; Keystone Correction (V=+/- 30°); LAN; Lens Shift (vertical 0.5 max., horizontal ± 0.1 max.); On/Off Timer; Plug&Play; Quick Lens Replacement and 5 Optional Lenses; Quick-Start-/Direct-Power-Off Function; Virtual Remote for direct PC control
Remote Control	Type RJ-45; Aspect Ratio; Automatic Picture Adjustment; Eco Button; Freeze-function; Help-function; Magnify-function; Page Control; Picture Mute; Source Select
Dimensions (W x H x D) [mm]	399 x 150 x 358 (without lens and feet)
Weight [kg]	7.4
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	381 Normal Mode; 334 Eco Mode; 0.5 Stand-by Mode
Calorific Value	max. 1351 BTU (1 KWh= 3,412.14 British Thermal Unit)
Fan Noise [dB (A)]	34; < 30 Eco Mode
Safety and Ergonomics	CE; TÜV GS; RoHS
Warranty	Projector: 3 years pan-European Service; Lamp: 6 Months, max. 1000 Hrs
Shipping Contents	Projector; IR remote control; Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Users Manual; CD-Rom with NEC Projector User Supportware; Lens Cap
Optional Accessories	Ceiling Mount Kit (NP30UCM); Hardcase (NP01TC); Lamp (NP06LP); Lenses: NP04ZL (3.0-4.8:1); Lenses: NP05ZL (4.7-7.2:1); Lenses: NP03ZL (1.9-3.1:1); Lenses: NP02ZL (1.2-1.5:1); Lenses: NP01FL (0.8:1)

[1] Compliance with ISO21118-2005

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 11/09

www.nec-display-solutions.co.uk

NEC Display Solutions UK Ltd, 1 Victoria Road , W3 6BL London
Phone: +4420899-38111, Fax: -27161, e-mail: info@uk.neceur.com