



compact ww242



>> **Ultra wide angle DLP™ projector**

The ultra wide angle lens allows projector positioning very close to the projection surface while keeping a full format picture.

>> **Ideal for interaction with interactive boards**

Minimum shadowing and zero dazzle in ceiling mounted projector installation via interactive board.

>> **Full brightness**

Bright mode at 3000 ANSI lumens and very high contrast ratio ensure a great picture, even at extreme picture sizes.

>> **Multimedia machine**

Integrated 8W speaker – no extra equipment necessary for multimedia presentations.

>> **Extended security features**

Extended theft prevention features such as a Kensington slot, security anchor, password protection and control panel lock.

>> **High connectivity**

Versatile connectivity options – digital and analogue PC inputs, video, S-video, component input via adaptor, two audio inputs, video and audio outputs.

>> **Virtually no maintenance**

DLP™ technology in filter free design eliminates filter cleaning and replacement.

Geha compact ww242 Technical Specifications

Order no.	-
Display technology	0,55"DLP
Resolution (physical)	XGA 1024 x 768 pixels, from VGA (640 x 480) to SXGA (1280x1024)
Brightness	3000 ANSI Lumen
Contrast ratio	3000: 1
Weight	4.3 kg
Dimensions (W x D x H)	339 mm x 276 mm x 122 mm
Noise level	30/28dB (Full/Eco)
Lens system	Fixed focus 6.97 mm/ F=2.59
Projection distance	0.5 m to 3.7 m
Image size (diagonal)	1.04 m to 7.72 m
Throw ratio	0.6:1 (distance to image width)
Offset	107%
Keystone correction	vertical +/-20° manual
Functions	digital keystone correction, ceiling mount, rear projection, digital zoom, quick start freeze, mask, OSD, password protection
Lamp	200 W P-VIP
Lamp life time (normal/economy mode)	3000h/4000h (eco)
Power supply	100 to 240V AC/ 50/60 Hz with phase compensation
Power consumption (on/stand-by)	280/<5 W
Video compatibility	PAL/SECAM/NTSC, 480i/p, 525i/p, 576i/p, 625i/p, 720p, 1080i
Horizontal frequency	15 to 91 kHz
Scanning rate	50 to 65 Hz
Bandwidth	-
Inputs	DVI-I, RGB (15 pin D-sub), Audio (1 x 3.5 mm jack), Video (RCA) S-video (1 x Mini-DIN 4pin), Component Video (via adapter), audio (1x3.5 mm pin)
Outputs	Monitor out RGB (1 x 15 pin D-sub), audio (1x3.5 mm pin)
RS232-Port	9 pin D-SUB
Mouse port	1x USB B
LAN port	-
Sound system	1 x 8 W
Standard accessories	Projector, lens cap, power cable 1.5 m, VGA cable, USB cable, remote control with batteries and mouse control, manual on CD ROM, quick start instructions card
Warranty	24 months
Lamp warranty	6 months or 1000 hours

Distributed by