

SAMSUNG L201W

General	
Width	29.1 cm
Depth	28.9 cm
Height	11.5 cm
Weight	3.8 kg
Enclosure Colour	Glossy white
Device Type	LCD projector
Built-in Devices	Stereo speakers
Expansion / Connectivity	
Interfaces	1 x VGA / component video input - 15 pin HD D-Sub (HD-15) 1 x S-video input - 4 PIN mini-DIN 1 x composite video input - RCA 1 x audio line-in - mini-phone stereo 3.5 mm 1 x VGA output - 15 pin HD D-Sub (HD-15) 1 x audio line-out - mini-phone stereo 3.5 mm 1 x audio line-out - RCA x 2 1 x serial RS-232C - 9 pin D-Sub (DB-9) 1 x HDMI - 19 pin HDMI Type A
Manufacturer Warranty	
Service & Support	3 years warranty
Service & Support Details	Limited warranty - 3 years
Miscellaneous	
Cables Included	1 x VGA cable
Security Features	Security lock slot (cable lock sold separately)
Power	
Power Device	Power adapter - internal

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	270 Watt
Power Consumption Operational (Standby)	1 Watt
Environmental Parameters	
Sound Emission	32 dB
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80%
Sound Emission (Economic Mode)	30 dB
Video Input	
Analogue video Signal	RGB, S-Video, composite video
Analogue Video Format	NTSC, SECAM, PAL, PAL-N, PAL-M, NTSC 4.43, PAL 60
Digital Video Standard	High-Definition Multimedia Interface (HDMI)
Video Modes	480p, 720p, 1080i, 480i, 576i, 576p
Audio Output	
Type	Speaker(s) - integrated
Sound Output Mode	Stereo
Speaker(s)	2 x right / left channel

Output Power / Channel	3 Watt
Input Device	
Type	Remote control - external - wireless
Projector / Panel	
Features	High-bandwidth Digital Content Protection System (HDCP), 16:9 aspect ratio support
Max Sync Rate (V x H)	75 Hz x 80 kHz
Throw Ratio	1.42 - 1.7:1
OSD Languages	English, German, French, Italian, Portuguese, Swedish, Russian, Spanish, Dutch, Chinese, Korean
Image Brightness	2000 ANSI lumens
Image Contrast Ratio	500:1
Image Size	102 cm - 762 cm
Bulb type	UHP 202 Watt
Projection Distance	1 m - 10 m
Controls / Adjustments	Keystone correction
Resolution	XGA (1024 x 768) (native) / 1600 x 1200 (resized)
Digital Zoom Factor	4x
Bulb life cycle	2500 hour(s) / 3000 hour(s) (economic mode)
Image Brightness (Reduced)	1700 ANSI lumens
Native Aspect Ratio	4:3
Video Output	

Analogue Video Signal	RGB
Projector Lens System	
Lens Aperture	F/1.65-1.93
Zoom Factor	1.2x
Vertical Keystone Correction	-20 / +20
Zoom Type	Manual
Focus Type	Manual
Keystone Correction Direction	Vertical