

# P1203 PROJECTOR

## DLP Technology – 3D Ready

The DLP® 3D ready Acer P1203 projector presents lifelike and breathtaking visuals for remarkable SMB/classroom presentations. Convenient utilities make this projector easy to set up, while advanced power-management solutions conserve energy and the Earth's resources.

### Why P1203 Projector?

- DLP® 3D ready
- Resolution Native XGA (1,024 x 768)  
Maximum UXGA (1,600 x 1,200),  
1080p (1,920 x 1,080)
- Contrast Ratio 3700:1
- Brightness 3,100 ANSI Lumens (Standard),  
2,480 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 39' (11.9m)



# Technical Specification

|                                        |                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model Name</b>                      | P1203 DLP® 3D Ready                                                                                                                                                                                                                                                                                |
| <b>Resolution</b>                      | Native XGA (1,024 x 768)<br>Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)                                                                                                                                                                                                                    |
| <b>Computer Compatibility</b>          | IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards<br>1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900),<br>WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050),<br>SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480) |
| <b>Video Compatibility</b>             | NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L),<br>HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)                                                                                                                                                                       |
| <b>Aspect Ratio</b>                    | 4:3 (Native), 16:9                                                                                                                                                                                                                                                                                 |
| <b>Contrast Ratio</b>                  | 3700:1                                                                                                                                                                                                                                                                                             |
| <b>Displayable Colours</b>             | 1.07 Billion Colours                                                                                                                                                                                                                                                                               |
| <b>Brightness</b>                      | 3,100 ANSI Lumens (Standard), 2,480 ANSI Lumens (ECO)                                                                                                                                                                                                                                              |
| <b>Projection Lens</b>                 | F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm<br>1:1.1 Manual Zoom and Manual Focus                                                                                                                                                                                                                       |
| <b>Projection Screen Size</b>          | 23" (58cm) ~ 300" (762cm)                                                                                                                                                                                                                                                                          |
| <b>Projection Distance</b>             | 3.3' (1.0m) ~ 39.0' (11.9m)                                                                                                                                                                                                                                                                        |
| <b>Throw Ratio</b>                     | 50"@2m (1.95 ~ 2.15:1)                                                                                                                                                                                                                                                                             |
| <b>Horizontal / Vertical Scan Rate</b> | 30k ~ 100k Hz / 50 ~ 120 Hz                                                                                                                                                                                                                                                                        |
| <b>Lamp Type / Life</b>                | Osram 230 W user replaceable P-VIP lamp<br>2,500 Hours (Standard), 4,000 Hours (ECO)                                                                                                                                                                                                               |
| <b>Keystone Correction</b>             | +/-40 Degrees (Vertical ), Manual & Auto                                                                                                                                                                                                                                                           |
| <b>Projection Mode</b>                 | Front, Rear, Front-Ceiling, Rear-Ceiling                                                                                                                                                                                                                                                           |
| <b>Ceiling Mounting Capability</b>     | Yes                                                                                                                                                                                                                                                                                                |
| <b>Audio</b>                           | One Internal Speaker with 2 watts Output                                                                                                                                                                                                                                                           |
| <b>IR Remote Control</b>               | IR remote control with laser pointer & PgUp/PgDn functions                                                                                                                                                                                                                                         |
| <b>Digital Zoom</b>                    | 2X                                                                                                                                                                                                                                                                                                 |
| <b>Power Supply</b>                    | AC input 100~240V auto-switching power supply                                                                                                                                                                                                                                                      |
| <b>Power Consumption</b>               | 290W Watts (Operation), <1 Watts (Standby)                                                                                                                                                                                                                                                         |
| <b>Operating Temperature</b>           | 5°C ~ 35°C / 41°F ~ 95°F                                                                                                                                                                                                                                                                           |
| <b>Noise Level</b>                     | 34 dBA (Standard mode), 31 dBA (ECO mode)                                                                                                                                                                                                                                                          |
| <b>Input Interface</b>                 | Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1,<br>S-Video (Mini DIN) x 1, HDMI (Video, Audio, HDCP) x 1, PC Audio (Stereo mini jack) x 1                                                                                                                                       |
| <b>Output Interface</b>                | Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1                                                                                                                                                                                                                                            |
| <b>Control Interface</b>               | USB (Type B) x 1, RS232 (Mini DIN) x 1, 12V DC (Screen control) x 1                                                                                                                                                                                                                                |
| <b>Dimensions</b>                      | 269 x 206 x 84 mm (10.6" x 8.1" x 3.3")                                                                                                                                                                                                                                                            |
| <b>Compliance</b>                      | C-Tick (AS/NZS 60950)                                                                                                                                                                                                                                                                              |
| <b>Standard Accessories</b>            | AC power cord, VGA cable, Remote control, Battery x 2 for remote control, Lens cap,<br>Carrying case, User's guide (CD-ROM), Quick start guide, Security card                                                                                                                                      |
| <b>Standard Warranty</b>               | 2 year return to base                                                                                                                                                                                                                                                                              |

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. \* Maximum hours. Actual hours depend on usage and configuration. \*\* Contact Acer for warranty details.