

**S5200**

<b>Display Technology</b>	DLP™, Digital Light Display with ColorBoost II + and EcoProjection
<b>Native Resolution</b>	Native XGA (1,024 x 768)
<b>Compressed Resolution</b>	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
<b>Typical colors</b>	134 Million Colors
<b>Brightness (ANSI lumens)</b>	3,000 ANSI Lumens (Standard) 2,400 ANSI Lumens (ECO)
<b>Dimension (WxDxH)</b>	290 x 254 x 99 mm (11.4" x 10" x 3.9")
<b>Weight</b>	7.7 lbs (3.5Kg)
<b>Contrast Ratio</b>	2500:1
<b>Noise Level</b>	33 dBA (Standard mode) 28 dBA (ECO mode)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,600 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 Native 16:9 compatible
<b>Picture in Picture Support</b>	N/A
<b>Projection Mode</b>	Front, Rear, Front-Ceiling, Rear-Ceiling
<b>Projection Lens</b>	F = 2.6, f = 7.50mm, Manual Focus
<b>Digital Zoom</b>	2X
<b>Projection Screen</b>	40" (102cm) ~ 300" (762cm)
<b>Throw Ratio</b>	161"@2m or 81"@1m (0.61:1)
<b>Projection Distance</b>	1.6' (0.5m) ~ 12.2' (3.7m)
<b>Horizontal Scan</b>	31.5-100KHz
<b>Vertical Scan</b>	56-120Hz
<b>Lamp Type</b>	Philips 210 W user replaceable UHP lamp
<b>Lamp Life</b>	4,000 Hours (ECO) 3,000 Hours (Standard)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical ), Manual
<b>Audio</b>	Two Internal Speaker with 5 watts Output
<b>Power Supply</b>	AC input 100~240V auto-switching power supply
<b>Power Consumption</b>	315 Watts (Operation) <1 Watts (Standby)
<b>Uniformity</b>	90%
<b>I/O Connectors</b>	Input interface: Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 AV Audio (RCA L/R) x 1 Output interface: Analog RGB (D-sub) x 1 PC Audio (Stereo mini jack) x 1 Control interface: RS232 (DE-9) x 1 Network interface: Ethernet port (RJ45) x 1
<b>Bundled Accessories</b>	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card

**Warranty**

All of Acer projectors support a two year carry-in warranty, five years warranty for the DM and one year warranty for the lamp.

---

**Configurations**

[S5200](#)

XGA, 3000 ANSI Lumens, 2500:1 Contrast Ratio, 0.61:1 Ratio, Carry Case, Remote, 3.5Kg

[EY.K1](#)