

BenQ

MP525P Digital Projector



- Filter-Free
- 2,500 ANSI Lumens
- Contrast 2600:1
- 1024x768 XGA
- 2W Speaker
- 28 dB




BenQ
Enjoyment Matters

BenQ Digital Projector MP525P

- Filter Free Design
- No Color Decay
- 2500 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- 6 Segments Color Wheel
- Keystone ±40°
- 2W Speaker
- Closed Captioning
- Panel Key Lock
- Quick Cooling
- Quick Auto Search
- Standby Power < 1W
- Security Password
- High Altitude Mode
- HDTV Compatible
- Auto Adjustment Hot Key

Specifications

Projection System	DLP® technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	2500 ANSI lumens	
Contrast Ratio	2600:1 (Full on/Full off)	
Keystone	Manual Vertical ±40°	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Lens	F=2.55 to 2.65, f=20.95 ~ 23.0 mm	
Zoom Ratio	Manual Zoom, 1.10:1	
Image Size (Diagonal)	24" to 300"	
Throw Ratio	1.86 - 2.04 (53"@2M)	
Lamp	210W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to UXGA(1600 x 1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-82 kHz	
Vertical Scan Rate	48-85 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 1
	A/V	Component Video: D-sub 15 pin x 1 (Shared with Analog RGB connector)
		S-Video: Mini Din 4 pin x 1
		Composite Video: RCA x 1
		Audio
Output Terminals	PC	Monitor Out: D-sub 15 pin x 1
	Audio	Variable Audio Out : Stereo Mini Jack x 1 Speaker: 2W x 1
Control Terminal	Serial Connector : RS232 9 pin x 1	
Dimensions(W x H x D)	10 x 3.5 x 8.4 inch (255 x 90 x 214 mm)	
Weight	4.8 lbs (2.2 kg)	
Power Supply	100 to 240 VAC, 50/60 Hz	
Power Consumption	275W, Standby < 1W	
Audible Noise	33/28 dB (Normal/Economic mode)	
On-Screen Display Languages	Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish	
	French / German / Hungarian / Italian / Japanese / Korean / Norwegian Polish / Portuguese / Romanian / Russian / Simplified Chinese / Spanish Swedish / Turkish / Thai / Traditional Chinese (24 Languages)	
Picture Modes	Dynamic Mode	Presentation Mode
	sRGB Mode	Cinema Mode
	User 1 Mode	User 2 Mode
Functions	BrilliantColor™	Quick Auto Search
	Closed Captioning	Wall Color Correction
	3D Color Management	Blank
	Resolution Reminder	Panel Key Lock
	Digital Zoom (x2)	Auto Off
	Freeze	Security Password
	HDTV compatible	"Q?" Hot Key for FAQ
	High altitude mode	Auto Adjustment Hot Key
	Quick Start Guide	VGA Cable
Accessories (Standard)	Manual CD	Power Cord
	Remote Control w/battery	
Accessories (Optional)	Presentation Plus	Spare Lamp Kit
	RS232 Cable	Soft Carry Case



Accessories (Optional)



Presentation Plus

Spare Lamp Kit




Ceiling Mount

Projection size

Screen size(inches)	40	60	80	100	120	150	200	300
Distance with max zoom(Min length)(mm)	1509	2264	3019	3774	4528	5660	7547	11321
Distance with min zoom(Max length)(mm)	1660	2491	3321	4151	4981	6226	8302	12453

There is 3% tolerance these numbers due to optical component verification.



Dealer's Stamp

BENQ

Enjoyment Matters