

Specifications MX711



Projection System	DLP® by Texas Instruments®
Native Resolution	XGA (1024 x 768)
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)
Brightness	3200 ANSI Lumens
Contrast Ratio	5300:1 (Full on / Full off)
Image Size	32" to 300"
Throw Ratio	1.5 to 1.97 (65" @ 2M)
Zoom Ratio	Manual Zoom, 1.3:1
Keystone correction	Auto Keystone Manual Vertical ± 40 Degree
Lens	F = 2.59 ~ 2.87
Lamp Life	230W, 3500 / 5000 hours (Normal / Economic mode)
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first
Operational Noise	32 / 27 dB (Normal / Economic mode)
Displayable Colours	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 5 aspect ratios selectable
Horizontal Frequency	31 ~ 92 kHz
Vertical Scan Rate	48 ~ 120 Hz
Input Terminals	PC: Analog RGB: D-sub 15 pin x 2 LAN networking: RJ-45 x1 (LAN Display) USB connector: - Type A x1 (USB thumb drive, mouse/ keypad control) - Type mini B x1 (USB display) AV: HDMI x1 S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 Microphone: Stereo Mini Jack x1 Audio L/R : RCA x 1 (set) Stereo Mini Jack x 1
Output Terminals	PC: D-sub 15 pin x 1 Audio: Variable Audio Out: Stereo Mini Jack x 1 Speaker: 10W x 1
Control Terminals	Serial Connector: RS232 9 pin (male) RJ45 x1 USB connector: Type mini B x1 (page up/down) shared
Video Compatibility	NTSC / PAL / SECAM
Dimensions (HxWxD)	104 x 311 x 244 mm
Weight	Net weight: 2.7 kg. Gross weight: 4.7 kg.

Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz
Power consumption	306W, Standby < 1W
On-Screen Display Language	Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian / Russian / Simplified Chinese / Spanish / Swedish / Turkish / Thai / Traditional Chinese (26 Languages)
Picture Modes	Dynamic Mode sRGB Mode Presentation Mode Cinema Mode User 1 Mode User 2 Mode
Functions	BrilliantColor™ Blank VIDI™ Panel Key Lock 3D Color Management Auto Off Crestron LAN Control Security Password Closed Captioning HDTV Compatible Digital Zoom (x2) High Altitude Mode Variable Audio Out "Q?" Hot Key for FAQ Quick Cooling 3D Ready Quick Auto Search Freeze
Included accessories	Quick Start Guide Manual CD Remote Control w/battery VGA Cable Power Cord Soft Carry Case
Accessories (Optional)	Presentation Plus Ceiling Mount Spare Lamp Kit Wireless Dongle
HDTV Compatibility	480i / 480p / 576i / 576p / 720p / 1080i / 1080p

Specification subject to change without notice