

## X1213

|                                   |                                                                                                                                                                                                                                                                                             |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Display Technology</b>         | DLP™, Digital Light Display                                                                                                                                                                                                                                                                 |
| <b>Native Resolution</b>          | Native XGA (1,024 x 768)                                                                                                                                                                                                                                                                    |
| <b>Compressed Resolution</b>      | Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)                                                                                                                                                                                                                                         |
| <b>Typical colors</b>             | 1.07 Billion Colors                                                                                                                                                                                                                                                                         |
| <b>Brightness (ANSI lumens)</b>   | 3,200 ANSI Lumens (Standard), 2,560 ANSI Lumens (ECO)                                                                                                                                                                                                                                       |
| <b>Dimension (WxDxH)</b>          | 280 x 230 x 84 mm (11" x 9.1" x 3.3")                                                                                                                                                                                                                                                       |
| <b>Weight</b>                     | 5.7 lbs (2.6 Kg)                                                                                                                                                                                                                                                                            |
| <b>Contrast Ratio</b>             | 4500:1                                                                                                                                                                                                                                                                                      |
| <b>Noise Level</b>                | 32 dBA (Standard mode), 28 dBA (ECO mode)                                                                                                                                                                                                                                                   |
| <b>Computer Compatibility</b>     | IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVG x 600), VGA (640 x 480)                     |
| <b>Video Compatibility</b>        | NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1 EDTV (480p, 576p), SDTV (480i, 576i)                                                                                                                                                                      |
| <b>Aspect Ratio</b>               | 4:3 Native, 16:9 compatible                                                                                                                                                                                                                                                                 |
| <b>Picture in Picture Support</b> | N/A                                                                                                                                                                                                                                                                                         |
| <b>Projection Mode</b>            | Front, Rear, Front-Ceiling, Rear-Ceiling                                                                                                                                                                                                                                                    |
| <b>Projection Lens</b>            | F = 2.56 ~ 2.8, f = 21.00mm ~ 23.00mm<br>1:1.1 Manual Zoom and Manual Focus                                                                                                                                                                                                                 |
| <b>Digital Zoom</b>               | 2X                                                                                                                                                                                                                                                                                          |
| <b>Projection Screen</b>          | 29" (73cm) ~ 300" (762cm)                                                                                                                                                                                                                                                                   |
| <b>Throw Ratio</b>                | 53"@2m (1.86 ~ 2.04:1)                                                                                                                                                                                                                                                                      |
| <b>Projection Distance</b>        | 3.9' (1.2m) ~ 37.2' (11.3m)                                                                                                                                                                                                                                                                 |
| <b>Horizontal Scan</b>            | 30k ~ 100k Hz                                                                                                                                                                                                                                                                               |
| <b>Vertical Scan</b>              | 50 ~ 120 Hz                                                                                                                                                                                                                                                                                 |
| <b>Lamp Type</b>                  | 230W user replaceable UHP lamp                                                                                                                                                                                                                                                              |
| <b>Lamp Life</b>                  | 4,000 Hours (ECO) - 2,500 Hours (Standard)                                                                                                                                                                                                                                                  |
| <b>Keystone Correction</b>        | +/-40 Degrees (Vertical ), Manual                                                                                                                                                                                                                                                           |
| <b>Audio</b>                      | One Internal Speaker with 2 watts Output                                                                                                                                                                                                                                                    |
| <b>Power Supply</b>               | AC input 100~240V auto-switching power supply                                                                                                                                                                                                                                               |
| <b>Power Consumption</b>          | 280 Watts (Operation), <1 Watt (Standby)                                                                                                                                                                                                                                                    |
| <b>Uniformity</b>                 | 85%                                                                                                                                                                                                                                                                                         |
| <b>I/O Connectors</b>             | Input Interface:Analog RGB/Component Video (D-sub) x 2<br>Composite Video (RCA) x 1<br>S-Video (Mini DIN) x1<br>PC Audio (Stereo mini jack) x 1<br>Output Interface:Analog RGB (D-sub) x 1<br>PC Audio (Stereo mini jack) x 1<br>Control Interface:USB (Mini-B) x 1<br>RS232 (Mini DIN) x 1 |
| <b>Bundled Accessories</b>        | AC power cord<br>VGA cable<br>Remote control<br>Battery for remote control<br>Lens cap<br>User's guide (CD-ROM)<br>Quick start guide<br>Security card<br>Carrying case (Optional)                                                                                                           |
| <b>Warranty</b>                   | All of Acer projectors support a two year carry-in warranty, five years warranty for the DM and one year warranty for the lamp.                                                                                                                                                             |

### Configurations

[X1213 3D](#) [EY.JB](#)  
X1213, XGA, DLP 3D, 4500:1, 3200Lm, ECO, CBII, Zoom, Bag, Auto Keystone, 2.6Kg, Top loading, 2 Year Fetch, Repair & Return Warra