

Give your presentations star quality with widescreen display and speakers



- Experience the incredible intensity of 3LCD
- Widescreen / normal screen size option
- 2 built-in stereo speakers
- Low operating noise level
- High Definition Multimedia Interface (HDMI)
- Access to Microsoft Office support




Stand out from the crowds with a higher level of professionalism with the L305 mobile data projector. The 3000:1 ANSI lumens and advanced 3-chip LCD technology delivers images that are of the highest quality, realistic and sharp. Colours are not only natural, but also bright and filled with detail. Put your presentation in good hands with the Samsung L305.



Experience the incredible intensity of 3LCD

3LCD technology reaches a new level of realism by using mirrors to split a white light source into primary colors—red, blue and yellow. Each color is then reflected onto its own LCD chip, which creates an image that combines into a vibrant full color image once it passes through a prism. The spectacular color image shoots through a lens and is projected onto the screen. What your eyes finally see is so unbelievably intense, it sets a new precedent in what you can expect from a projector.

Clear, focused images




You can select between wide screen (16:9) and normal screen (4:3) sizes to help you present perfectly focused images that fully fit your needs.

H/V Keystone capability



Keystones occur when a projector is not placed exactly in the center of a projection screen, causing image stretching and distortion. When the projector is placed either above or below center, Vertical Keystones occur. Horizontal Keystones occur when the projector is at an angle either to the left or right of center. The Samsung Projectors offer effective Keystone Correction, compensating for imprecise projector placement and delivering perfectly presented projections that appear accurate and exact. Vertical Keystone Correction is in-built on all models; Horizontal Keystone Correction is included on the L305.

Powerful stereo sound



The Samsung projectors are the ultimate professional data projectors. With powerful built-in stereo speakers (3W x 2), they exude an air of complete professionalism that adds depth and resonance to presentations.

Low noise



Noise level is almost inaudible in normal living environments. User satisfaction is maximized with low noise design that meets highest standard.

Comprehensive connectivity



The Samsung projectors come equipped with a full range of input options that allow you to connect with a full range of digital multimedia devices. The HDMI (High Definition Multimedia Interface) enables the highest resolution images to be transmitted with 100% integrity for a truly breathtaking visual experience.

PC-Free Microsoft Office support



The Samsung L305 is designed to enable high-impact presentations to be projected with speed and simplicity. The PC-Free Office Viewer gives automatic access to Microsoft Office applications via simple USB plug-and-play operation, enabling you to enjoy powerful and professional portable projection.

General	Audible Noise	Eco-Mode: 30 dB, Normal-Mode: 32 [dB]
	Actual Dimension (WxDxH, mm)	291 x 289 x 115mm
	Actual Weight (kg)	3.8kg
	Shipment Dimension (WxDxH, mm)	402 x 370 x 179mm
	Shipment Weight	5.4kg
	Projector Warranty	3 years
	Lamp Warranty	6000 hours / 1 year
	Operating Temperature	5 - 35°C
	Max Altitude Supported	Max 3000m (Operating)
	Operating Humidity	20% - 80% (Non-condensing)
	Typical Power Consumption	290 Watts
	Standby Power Consumption	Under 1W
	Max Power Consumption	Under 300 Watts
	Power Supply	100 - 240 Volts at 50 - 60Hz

	Menu Language	English, German, Netherlands, Spanish, French, Italiano, Swedish, Portuguese, Russian, Turkish, Tai, Chinese, Korean
	Approvals	UL and c-UL (US/Canada), FCC-B (US/Canada), CE (CE member countries), CCC (China)
Pictures	Brightness (Typical)	3000 ANSI
	Contrast Ratio (Typical)	500:1
	Resolution	XGA
Display	Native Aspect Ratio	4:3
	Supported Aspect Ratio	4:3, Zoom1, Zoom2, 16:9
	Brightness (Max ANSI lumens)	High Bright: up to 3000 ANSI Lumens Up to 500:1 Full On / Off
	Display Technology	3 panel LCD(p-Si TFT Active-matrix)
	Data Compatibility	VGA, SVGA, XGA, SXGA, UXGA
	Video Compatibility	NTSC, NTSC-4.43, PAL, PAL-M, PAL-N, PAL-60, SECAM480i, 576i, 480p, 576p, 720p, 1080i
	Native Resolution	XGA
	Projector Placement	Front Floor, Front Ceiling, Rear Floor, Rear Ceiling
	Lamp Type	UHP Lamp
	Lamp Wattage	High Bright: 220 Watts / Eco Mode: 172 Watts
	Lamp Life	High Bright: 2000 Hours / Eco Mode: 2500 Hours
	Picture Mode	Dynamic, Standard, Presentation, Text, Movie, Game, User
	Screen Format	Normal / Zoom1 / Zoom2 / 16:9
	Minimum Image Size	40"
	Max Image Size	300"
Standard Lens Zoom	1.2 : 1	
Standard Lens Throw Ratio	1.43 - 1.71	
Standard Lens Image Offset Ratio	67%	
Standard Lens Projection Distance	1 - 10m	
Digital Keystone Correction (V)	+/- 20°	
Digital Keystone Correction (H)	Not Available	
Input & Output	DVI	(Requires HDMI to DVI cable)
	HDMI	Number of Inputs: 1
	Component (RCA)	(Requires D-sub to RCA component cable)
	Computer	Number of Inputs: 1 (D-sub 15pin)

	S-Video	Number of Inputs: 1
	Composite (RCA)	Number of Inputs: 1
	HDCP Support	Yes
	RS-232	Yes (D-sub 9pin)
	USB	No
	Stereo RCA Jacks Input	Number of Inputs: 1 (pair with S-Video or Composite RCA)
	Stereo 3.5 mm Mini-jack Input	Number of Inputs: 1 (pair with D-sub 15pin)
	Projector Control	Projector Key panel, Remote Control
	Speaker	Stereo 2 speaker (3W x 2)
	Monitor Output	Number of Inputs: 1 (D-sub 15pin)
	Audio Output	Not Available
Compatibility	Data Compatibility	VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), SXGA (1280 x 1024), UXGA(1600 x 1200)
	H-Sync Range	30 - 80 [KHz]
	V-Sync Range	56 - 75 [Hz]
		NTSC, NTSC-4.43, PAL, PAL-M, PAL-N, PAL-60, SECAM480i, 576i, 480p, 576p, 720p, 1080i
	Product Color	White

Features and specifications are subject to change without prior notification.