

# SHARP®

## Conference Series P25



XG-P25X

With an eye popping **4000 ANSI lumens** this LCD projector can be used in a wide variety of presentation scenarios. Mount it on the ceiling for use in conference rooms and board rooms. Take it from room to room for collaborative work group sessions. Travel with it on the road, afterall, its light enough and durable.

Sharp's **Conference Series P25** has wide compatability, versatility, and is an outstanding performer. With multiple inputs and outputs, this projector can create a true multimedia experience. Incorporate computer sources, video sources, and audio to mesmerize your audience and leave a lasting impression.

Just one of several projectors in Sharp's Conference Series family, **Conference Series P25** includes image resizing technology for compatibility with a wide range of resolutions, digital motion correction for crisp video, presentation tools for ease of use, digital keystone correction and auto sync technology for simple set up, and much more. You'll see, its more than you bargained for!

### ADVANCED FEATURES

- \* 4000 ANSI Lumens Brightness with 85% Uniformity (CCR)
- \* Multiple Inputs for Computer, Standard and HD Video Applications
- \* HDTV Compatible - 480i / 480P / 580i / 580P / 720P / 1035i / 1080i (4:3 & 16:9 aspect ratios)
- \* Separate Composite and S-Video Inputs
- \* Two (2) Component Video Inputs via RGB terminals
- \* RS-232C Compatability with remote systems
- \* Superior Video Quality: 3D Y/C circuitry, digital comb filter, digital noise reduction, Interlaced or Progressive scan, digital motion correction
- \* Advanced ImageACE Resizing - Supports Resolutions up to UXGA!
- \* Power Save Function for reduced power consumption and fan noise
- \* Manual Lens Shift; 1.3:1x Power Zoom/Focus Lens
- \* Variable or Fixed Audio Output

### PROJECTION DISTANCES

Standard Lens Throw Ratio - 1:1.8 - 2.4

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	4'6"	6'2"
60"	48"	36"	7'2"	9'2"
72"	58"	43"	8'5"	11'2"
84"	67"	50"	10'2"	13'1"
100"	80"	60"	12'1"	15'7"
150"	120"	90"	18'4"	24'"
200"	160"	120"	24'6"	32'2"
300"	240"	180"	37'4"	48'2"

Approx. Min / Max Projection Distance from Screen to Front of Lens  
To determine Min / Max Throw Distance multiply the screen width in feet by the throw ratio. Calculations are not linear, therefore, there may be an error of +/- 3%.

### SPECIFICATIONS

Resolution	XGA (1024 x 768) / 750 TV Lines
Panel Type	3 - 1.3" Polysilicon TFT LCD
H & V Frequency	fH 15-126 kHz / fV 43 - 200 Hz
Dot Clock	12 - 230 MHz
PC Compatibility	XGA (VGA to UXGA w/ ImageACE Resizing)
Mac Compatibility	1024 x 768 (up to 1280x1024 w/ImageACE Resizing)
WS Compatibility	1024 x 768 (various modes w/ImageACE Resizing)
Video System	NTSC/PAL/SECAM-interlaced or Progressive Scan
HD Compatibility	480i / 480P / 580i / 580P / 720P / 1035i / 1080i 4:3 & 16:9 Aspect Ratios
Resizing	Advanced ImageACE Resizing - up to UXGA
Brightness	4000 ANSI Lumens w/85% CCR / LPM 3400 AL
Contrast Ratio	600:1
Lens Type	1.3:1x Power Zoom and Focus w/Manual Lens Shift
PC Control	RS-232C - 9 pin D-Sub In/Out
Remote Control	IR (Carrier Frequency 38kHz)
Wired Remote	3.5 mm Minijack
Audio System	2 Watt Stereo
Lamp	AC 270 Watt, User-replaceable / LPM 235 Watt
Lamp Module Part No.	BQC-XGP25/1
Fan Noise	37 dB / LPM 35 dB
Power Source	100-240V AC, 50/60Hz
Power Consumption	380 Watts / LPM 350 Watts / Standby 0.7 Watts
Power Dissipation	<1430 BTU / Hour
Presentation Tools	"PresenterPAK"
Dimensions	12.5" x 16.6" x 6.1"
Weight	21.4 lbs.
Limited Warranty	3 Years Parts / Labor 3 Years Sharp ER, Lamp 90 days

### INPUTS/OUTPUTS

- 2 - Computer / RGB / Component Inputs [(1)15pin HD, (1)5 BNC ]
- 2 - Video Input [Composite (RCA); S-Video (4 pin DIN)]
- 3 - Stereo Audio Inputs (1, RCA pair L/R; 2, 3.5mm Stereo Minijacks)
- 1 - Computer / RGB Output [15pin HD]
- 1 - Audio Output (3.5mm Stereo Minijack)
- 1 - Control Input & Output - Multi Addressable via Bi-directional RS-232 (9 Pin D-Sub x2)
- 1 - Wired Remote Control Input (3.5mm Minijack)
- 1- DVI-I Input - 29 Pin (DigitalRGB, Analog RGB)

### INCLUDED ACCESSORIES

10' RGB Signal Cable, 10' Minijack Audio Cable, 12' Grounded AC Cord, Sharp Advanced Professional Presentation Software 1.5, S.A.P.S. Installation Instruction Sheet, 3 BNC/RCA Adapters, Quick Reference Cards, Wired/Wireless Remote, Extra Air Filter, 2 AA Batteries, Operation Manuals

### OPTIONAL ACCESSORIES

- AN-P200BAG** Soft Sided Carry-on Bag (projector only)
- AN-P200WCC** Hard Shell Carry Case w/wheels (projector only)
- AN-P200SC** "ATA" Shipping Case w/wheels (projector only)
- AN-XGCM61** Ceiling Mounting Bracket
- AN-EP101B** Extension Tube for Ceiling Mount
- AN-JT200P** Angle Mount Joint for Ceiling Mount
- AN-P9MX** Wide Angle, Fixed Focus Lens - 1:0.9 throw ratio
- AN-P48EZ** Long Throw Zoom Lens - 4.8-6.0 throw ratio
- AN-T6EZ\*** Telephoto Zoom Lenx - 2.5 - 3.2:1 throw ratio
- AN-W6EZ\*** Wide Angle Zoom Lens - 1.3 - 1.7:1 throw ratio

\* Bayonet mount part #CLNS-0236CE01 is required / sold separately.

Design and specifications are subject to change.  
All trademarks are property of their respective holders.

SHARP ELECTRONICS CORPORATION  
LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135  
E-mail: ProLCD@SharpSEC.com  
**1-888-GO-SHARP**  
[www.SharpLCD.com/Conference](http://www.SharpLCD.com/Conference)  
Printed in USA LC-02-241 02/02 Rev 09/02

**SHARP**  
be sharp®

