



PLC-WL2503



- Ultra-short Focus Projector for short-distance-projections
- Embedded Interactivity: presentations can be adjusted and controlled in real time using an interactive pen
- Multimedia projector with built-in 10 Watt speaker
- Brightness: 2.500 ANSI lumens, contrast ratio: 500 : 1
- WXGA Resolution (1.280 x 800 pixels) in 16 : 10 format
- Black-board mode for optimised projections onto coloured surfaces (e.g. interactive whiteboards)
- Direct Power On/Off allows switching the projector on/off without delay
- Anti-theft function through PIN code lock, Key lock
- MyLogo Function for custom logo transfer
- 3 years warranty, 1 year lamp warranty (max. 2,000 hours)

PLC-WL2503

TECHNICAL DATA	PLC-WL2503
EAN Code	4994334286284
Category	Business & Education
Panel	3 x 0.59" TFT p-Si (16:10) with micro lens, Organic LCD panel
Lamp	230 W NSH (LMP-141)
Brightness	2500 ANSI lumens, 1900 ANSI lumens (eco mode)
Lamp life	4000 h (eco mode) / 3000 h (normal mode)
Fan noise	29 dB (eco mode) / 36 dB (normal mode)
Standard lens	F = 1.8 / f = 6.68 mm *
Throw distance ratio	0.5 : 1
Throw distance	0.64 - 1.20 m
Contrast ratio	500 : 1
Resolution in pixels	1,280 x 800 (WXGA)
Image size min. - max. (diagonal)	60 - 110 inch
Uniformity	80 %
Bandwidth/Frequency	140 MHz, Horizontal frequency: 15 - 100 kHz, Vertical frequency: 50 - 100 Hz
Color systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: HDMI (HDCP) Input 2: D-Sub15 (RGB/component) Input 3: D-Sub15 (RGB) or monitor out Input 4: RCA (composite) Input 5: Mini DIN 4 (S-Video) Audio: 3.5 mm stereo jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm stereo jack Control input jack 1: RJ45 (LAN) Control input jack 2: D-Sub9 (RS232)
Audio function	10 W mono
Keystone correction	vertical +/- 20°
Up/Down ratio	10 : -1.68 (fixed U/D ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i, 1,080p
Computer compatibility	UXGA / SXGA / SXGA+ / WXGA / XGA / SVGA / VGA / WXGA+ / WSXGA+ / WUXGA
Power consumption / Voltage	217 W (eco mode) / 316 W (normal mode) / 0.8 W (stand-by mode) / 100 - 240 V
Unique features	Ultra-short focus projector, Longlife-filter, Interactive function, Eco mode, Power management, Automatic set-up (input search, keystone-correction, auto PC adjustment), Multi scan system, Keystone correction, Direct Power On/Off, Digital zoom, Black-board mode, Color-board mode, MyLogo function, Freeze function, No Show mode, Picture reverse function, Picture inverse function, Progressive scanning 2-3/2-2 pull down, Key lock function, PIN code lock, Security bar, Kensington lock, Presentation timer, Web management function, Email error reporting, Network capability/LAN, SNMP log function, Multi language menu
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	350.0 x 143.4 x 381.9 mm
Weight (net)	4.7 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, USB cable, D-Sub15 cable, PIN code label, Lens cover with cord, Software for interactive function (CD-ROM), Interactive pen, Interactive pointer, Longlife-filter
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART), Components/D-Sub15 cable (POA-CA-COMPVGA), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03), Wall mount (POA-WMST01)
Lenses	Standard lens

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances

Technical specifications subject to change without notice. Date 02/2011

