

**Dell 4320 Projector****PROJECTION****Brightness:**4300 ANSI Lumens<sup>8</sup> (Max.)**Contrast Ratio:**

2000:1 Typical (Full On/Full Off)

**Resolution:**

WXGA (1280 x 800)

**Uniformity:**

80% Typical (Japan Standard - JBMA)

**Projection Lens:**

F-Stop: F/2.4~2.66

Focal length, f = 18.2~21.8mm

**Throw Ratio:**

1.28 (wide) -1.536 (tele)

**Lens Offset:**

112.4 ± 5%

**Image Size:**

At 3.94 ft (1.2m) distance, diagonal projection image size of 36.3" (0.92m).

At 32.81 ft (10m) distance, diagonal projection image size of 362" (9.2m).

**Projection Distance:**

3.94 ft ~ 32.81 ft(1.2m ~ 10m)

**CONNECTIVITY**

AC power input socket

2x 15-pin D-Sub for analog RGB/component input signals

1x 15-pin D-Sub for VGA-A loop through

1x Composite Video RCA jack for CVBS signal

1x 4-pin S-Video for Y/C signal

1x mini USB-B slave for remote support and firmware update

1x USB-A for USB Viewer

1x USB-B for USB Display

USB Wi-Fi connector for optional wireless functionality (USB wireless dongle sold separately)

2x 3.5mm stereo mini phone jack and 1x pair of RCA

connectors (left/right) for audio input

1x 3.5mm stereo mini phone jack for audio output

1x RJ45 connector for networking

1x HDMI 1.3 (HDCP compliant)

1x mini-DIN 6-pin RS232 port allows connection to a

commercial RS232 control box for remote projector control

1x DC jack 12V @200mA output, relay control for automatic projection screen control

**LAMP****Lamp Life Cycle<sup>5</sup>:**

Up to 2,000 hours Typical

Up to 2,500 hours Eco-Mode

**Lamp Type:**

Philips 300W user-replaceable

**VIDEO COMPATIBILITY**

Composite Video / S-Video input: NTSC [J, M, 4.43] PAL (B, D, G, H, I, M, N, Nc, 60) SECAM (B, D, G, K, K1, L)

Component Video via VGA input: 480i/p, 576i/p, 720p, 1080i

Component Video via HDMI input: 480i/p, 576i/p, 720p, 1080p

**AUDIO**

2x 5W speaker RMS

**KEYSTONE CORRECTION**

Manual Vertical +40° / -35°

**SECURITY**

Kensington lock slot (security cable sold separately)

Password protection

**SIZE AND WEIGHT****Dimensions (W x H x D):**

11.26" x 4.33" x 9.76" (286 x 110 x 247.8 mm)

**Weight:**

6.4 lbs (2.9 kg)

**Environmental and Regulatory****ELECTRICAL****Power:**

Universal AC 100-240 50-60Hz with PFC input

**Power Consumption Operational:**

Full Mode: 375W ± 10% @ 110Vac (network on)

Eco-Mode: 320W ± 10% @ 110Vac (network on)

Power-Saving Mode: 10W (wireless &amp; network on)

Standby Mode: 0.5W (network, VGA Out, &amp; wireless off)

**ENVIRONMENTAL****Operating temperature:**

5°C - 35°C (41°F - 95°F)

**Humidity:**

80% (maximum)

**Storage temperature:**

0°C - 60°C (32°F - 140°F)

**Humidity:**

90% (maximum)

**Shipping Temperature:**

-20°C - 60°C (-4°F - 140°F)

**Humidity:**

90% (maximum)

**WHAT'S IN THE BOX**

Power Cable

VGA Cable

Carry Case

USB cable

CD User's Guide

Remote Control with 2 AAA Batteries

Quick Setup guide &amp; Product Information guide