

# NEC M420X

ORDER CODE: 60003131

NEC M420X Multi-Purpose Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. The M420X is particularly suited for big classrooms and big meeting rooms.



## DELIVERING GENUINE BENEFITS

**Get Great Performance** while not compromising on quality and ease of use.

**Save the Environment** with latest Eco technology by minimizing your power consumption and consumables replacements.

**Large Flexibility** in positioning the projector and minimized cost for replacements.

**Intuitive Use** of latest Eco and projection technology due to user-centric design.

**Peace of Mind** with future-proof connectivity.



**HDMI**<sup>™</sup>  
HIGH DEFINITION MULTIMEDIA INTERFACE



## OUTSTANDING PERFORMANCE

- **Maximum Flexibility** with large 1.7x optical zoom
- **Minimized Cost of Ownership** due to long lamp life and filter cleaning intervals
- **Innovative ECO Functions** to reduce power consumption
- **Great Connectivity** due to numerous analog and digital connection terminals as well as network capability
- **Intuitive and Easy Operation** with user centric design and lens cover



**SPECIAL CHARACTERISTICS**

Auto Eco Mode; Auto Power ON/OFF; Automatic and manual Keystone Correction (V= +/-30°); Carbon Savings Meter; Colour Management; Content Transmission via Network; Control and administration via LAN; DICOM Simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; lens cover; Magnify; Off-Timer; Optional User Logo; Optional WLAN; OSD with 27 languages; Password Security System; Quick On/Off; RS-232 Control; Security Bar; USB Display; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction



**ECO Innovation:** Auto ECO Mode; Green one touch ECO and AV mute button; 75% AV mute function

**Energy Efficiency:** ECO scheduler; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling

**Ecological Materials:** 100% recyclable packaging; Downloadable manuals; ECO packaging

**Ecological Standards:** RoHS compliant; ErP compliant

Technical Specification NEC M420X	
<b>IMAGE</b>	
Display	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA
Native Resolution	1024 x 768 (XGA)
Brightness <sup>1</sup>	4200 ANSI Lumen (approx. 75% in Eco Mode)
Contrast Ratio <sup>1</sup>	2000:1
Lamp	265 W AC (195 W AC Eco Mode)
Lamp Life [hrs]	3000 (3500 Eco Mode)
Lens	F= 1.7-2.1, f= 17.5-29.0 mm
Projection Factor	1.3 - 2.2 : 1
Projection Distance [m]	0.6 - 13.8
Screen Size (diagonal) [cm]	Minimum: 63.5 / 25"; Maximum: 762 / 300"
Zoom	Manual
Focus Adjustment	Manual
Supported Resolutions	1152 x 870 (MAC 21"); 1440 x 900 (WXGA+); 1360 x 768 (WXGA); 1366 x 768 (WXGA); 720 x 576 (SDTV 576p/576i); 1680 x 1050 (WSXGA+); 1600 x 900 (WXGA++); 1400 x 1050 (SXGA+); 1280 x 1024 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 720 x 480 (SDTV 480p/480i); 1600 x 1200 (UXGA); 1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1152 x 864 (XGA); 1024 x 768 (XGA); 800 x 600 (SVGA); 832 x 624 (MAC 16"); 640 x 480 (VGA/MAC 13"); 720 x 576 SDTV 480p/480i; 720 x 480 SDTV 576p/576i; SDTV 480p/576p
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz
<b>CONNECTIVITY</b>	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
Video	Input: 1 x RCA
HDMI®	Input: 1 x HDMI® (Deep Color, Lip sync)
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; Input: 2 x RCA Stereo; Output: 1 x 3.5 mm Stereo Mini Jack (variable)
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	2 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
<b>REMOTE CONTROL</b>	
Remote Control	Source Select; Auto Adjust; Aspect Ratio; Picture Adjust; Audio Control; Picture Mode; Freeze; Help Eco Mode; Digital Zoom; Presentation and Mouse Control; AV Mute; ID set
<b>ELECTRICAL</b>	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	343 (Normal) / 264 (Eco) / 8 (Network Stand-by) / 0.4 (Stand-by)
<b>MECHANICAL</b>	
Dimensions (W x H x D) [mm]	398 x 115 x 282 (without lens and feet)
Weight [kg]	3.6
Fan Noise [dB (A)]	30 / 36 (Eco / Normal)
<b>ENVIRONMENTAL CONDITIONS</b>	
Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80
<b>OPTIONAL ACCESSORIES</b>	
Optional Accessories	Lamp (NP17LP); Wireless LAN module (NP02LM2); Cable Cover (NP01CV)
<b>ERGONOMICS</b>	
Safety and Ergonomics	CE; TÜV GS; ErP; RoHS; Gost-R
Speakers [W]	1 x 10 (mono)
<b>WARRANTY</b>	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
<b>SHIPPING CONTENT</b>	
Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Utility software; Security Sticker; Users Manual on CD-ROM; Quick Setup Guide

<sup>1</sup>Compliance with ISO21118-2005