

### Highlights

- Ideal for Home Entertainment
- Easy setup
- Easy Maintenance

Projection System	DLP			
Native Resolution	1080p(1920×1080)			
Brightness	2000 ANSI lumens			
Contrast Ratio	5000:1			
Display Color	1.07 Billion Colors			
Lens	F=2.50~2.76, f=23.5~28.2mm			
Aspect Ratio	Native 16:9 (5 aspect ratio selectable)			
Throw Ratio	1.59-1.9 (56.8"@2m)			
Image Size (Diagonal)	28" to 300"			
Zoom Ratio	1.15:1			
Lamp Type	190W			
Lamp (Normal/Economic Mode)*	4500/6000 hours			
Keystone Adjustment	ID, Vertical +/- 40 degrees			
Projection Offset	130%+-5%			
Resolution Support	VGA(640 × 480) to 1080p(1920 × 1080)			
Horizontal Frequency	31K~90KHz			
Vertical Scan Rate	48~86Hz			
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Companionicy	Video Compatibility	NTSC, PAL, SECAM		
Interface	Computer in (D-sub 15pin)	x I		
	Composite Video in (RCA)	x l		
	S-Video in (Mini DIN 4pin)	x l		
	Component Video in	x I (RCA x 3)		
	Audio in (Mini Jack)	x I		
	Audio L/R in (RCA)	x 2		
	Audio out (Mini Jack)	x l		
	Speaker	10W x I		
	HDMI VI.3	x 2		
	USB (Type Mini B)	x I (USB Download & Page up/down)		
	RS232 (DB-9pin)	x I		
Dimensions	Dimensions(W x H x D)	330 x 247 x 150 mm		
Differsions	Weight	3.6 kg (7.9lbs)		
Power	Power Supply	100 to 240 VAC, 50 to 60 Hz		
lower	Power Consumption	270W, Standby<1W		
Audible Noise	31/28 dBA (Normal/Economic mode)	27011, Stalldby 1111		
On-Screen Display Languages		Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/Italian/ Indonesian/		
On-screen Display Languages	Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/			
	Traditional Chinese (26 Languages)			
Picture Modes	Bright/Living Room/Gaming/Cinema/User 1/User 2/User3			
Accessories	Standard	Optional		
Accessories	Remote Control w/ Battery	Spare Lamp Kit P/N: 5J.J5405.001		
	Power Cord (by region)	Ceiling Mount P/N: 5J.J2K01.001		
	User Manual CD	Cenning Product P/IN: 3J.JZK.01.001		
	Quick Start Guide			
	Warranty Card (by region)			
	VGA(D-sub 15pin) Cable			

<sup>\*</sup>Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

#### **Distance Chart**

will add in at next version

# Wall mount/Ceiling mount Chart

will add in at next version

## **Dimension**





