

EW675UT – Ultra Short Throw

- Native WXGA, 60" image from just 39cm away
- Shadow-free images on interactive whiteboards
- Bright images, vivid colours – 3200 ANSI Lumens
- Crystal-clear images – HDMI connectivity
- Crestron RoomView® – RJ45 network control and monitoring
- Impressive sound quality – integrated 10W speaker
- 3D-Ready technology – DLP®-Link™ enabled
- Environmentally friendly design – less than 0.5W standby mode



3D projection in the smallest of rooms with the EW675UT

The WXGA ultra short throw, 3D-Ready EW675UT is designed to display bright, rich, colourful, crystal-clear images for both the education and business environments. Perfect for installations with interactive whiteboards ensures teaching and business environments have the right tools for engaging and presenting to their audience without shadows and screen glare. The EW675UT at 3200L incorporates extensive connectivity, powerful 10W stereo speakers and RJ45 control to maintain and monitor the projectors over the network.

The environmentally friendly EW675UT has energy saving features including less than 0.5W standby mode and auto power off saving you both time and money. Our unique Optoma Colour and Imager guarantees ensure hassle-free, long-lasting projection.

SPECIFICATIONS

Brightness	3200 ANSI Lumens
Contrast Ratio	3000:1
Native Resolution	WXGA 1280 x 800
Compatible Resolutions	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA
Display Technology	0.65" XGA DC3 DLP® chip, Technology by Texas Instruments
Lamp Life	2500/2000 hours (STD/BRIGHT mode)
Remote Control	Full function remote with mouse control and direct source selecting

INPUTS

HDMI (HDCP)		
2 x 15 Pin D-Sub VGA		SCART via adaptor Component via adaptor
S-Video 4 Pin Mini Din		
Composite RCA Jack		
3 x Audio In	3.5mm Audio Mini Jack RCA L&R	

CONTROL

USB (remote control)
RS232 3 Pin Mini Din
RJ45

OUTPUTS

PC 15 Pin D-Sub VGA (monitor loop-through)
Audio Mini Jack
+12v Trigger

PROJECTION LENS

	F Number	-
	Focus Length	-
	Focus / Zoom	Manual Focus / Digital Zoom ??
	Throw Ratio	0.3 (Projection Distance:Image Width)
Projection Distance		0.3 – 2.5m
Image Size		60" @ 37cm - Diagonal 16:10
Offset		127% ±5%
Audio		10W Speaker
Aspect Ratio		16:10 Native, 4:3 compatible
On Screen Display		19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Farsi and Arabic
Video Compatibility		PAL SECAM 625/576i/p, NTSC 525/480i/p HD 720p/1080i/p
Keystone Correction		± 35° Vertical
Horizontal / Vertical Scan Rate		15 – 97kHz / 25 – 85Hz
Power Supply		100 – 240V, 50 – 60Hz
Operating Conditions		5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max)
Security		Security Bar, Kensington Lock Port, Password Protection
RoHS		Compliant
Lamp Warranty		6 months or 1000 hours – whichever comes sooner
Warranty		Warranty will vary by country. Please see www.optomaeurope.com or ask your local supplier for details
Colour Guarantee		5 Years
Imager Guarantee		5 Years

