

ViewSonic® PJ755D Projector

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR



Brilliant, life-like colour for powerful video

The ViewSonic PJ755D DLP multimedia projector delivers brilliant colour, sharp graphics and outstanding video. With 2,700 lumens, 2000:1 contrast ratio and 1024 x 768 optimum resolution, you'll be impressed by this **PROJECTOR'S RICH SATURATED COLOUR AND INCREDIBLY SMOOTH VIDEO**. With digital (DVI) and analogue (VGA) inputs and support for HDTV signals you can deliver professional multimedia presentations in the office or view stunning, life-like DVDs and videos at home. Unlock the power of the **ULTRABRIGHT, HIGH PERFORMANCE** PJ755D in your home or office.



Stunning colour and clarity.

... Bright in virtually any setting

Packs 2700 lumens in just 3.4kg, the choice of professionals for high brightness.

... Supports HD signals including 720p and 1080i

Capable of displaying HD signals as well as other video and data sources.

... Easy set-up and auto tuning

One-touch setup button for fast, easy sync and sharp focus.

... OnView® controls plus ViewMatch® colour for superior screen adjustability

... The perfect image in any setting

Digital keystone correction, short focal length and zoom function ensure the perfect size image in any room.

... Whisper-mode extends lamp life

Extend the life of your lamp up to 4000 hours² and reduce noise output.

... Ultimate flexibility with multiple inputs

Rich connectivity with RGB, DVI, component video, composite video and S-video inputs and a monitor output.



*Easy-to-use
fully functional wireless
remote control included.*

ViewSonic®



Super bright

ViewSonic® PJ755D Projector

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR



- 1. Stand by/on
- 2. Menu
- 3. PC/video inputs, outputs and monitor pass through and RS-232
- 4. Kensington security port
- 4. Zoom and focus rings

Image Size (Diagonal cm, Wide - Telephoto)	Height (cm, Wide - Telephoto)	Width (cm, Wide - Telephoto)	Throw Distance (cm)
76 - 63	46 - 38	61 - 51	119
188 - 157	112 - 94	150 - 124	300
312 - 262	188 - 157	249 - 208	500
437 - 366	262 - 218	351 - 292	701
500 - 417	300 - 249	401 - 333	800
612 - 521	376 - 312	500 - 417	1001

Accuracy of the calculations are +/- 5%.

XGA PORTABLE DLP PROJECTOR

DLP	Type Pixel Format Lens Zoom Factor Keystone	0.7" XGA Digital Micromirror Device (DLP™) 1024 x 768 XGA (native resolution) Manual zoom/focus 1.2 Vertical ± 16°, horizontal ± 5°
DISPLAY	Size Throw Distance Throw Ratio Lamp Brightness Contrast Ratio Aspect Ratio	24.6" - 246" (Diagonal) 1.2m - 10m 2 ~ 2.4:1 250W, 4000 hours ² 2700 lumens 2000:1 4:3 (native), 16:9
INPUT SIGNAL	Video Frequency	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576p, 720p, 1080i) F _H : 15-100KHz; F _V : 43-120Hz
COMPATIBILITY	PC Mac ³	Analogue: from VGA up to UXGA (scaled) Analogue: up to SXGA
CONNECTOR	RGB (input) DVI (input) RGB (output) Component Video (input) Composite Video (input) S-Video (input) Control USB	DB-15 (x1) DVI (x1) DB-15 (x1) RCA jack (x1 set) RCA jack (x1) Mini-DIN 4-pin (x1) RS-232 (mini-DIN, 3-pin) USB for remote
POWER	Voltage Consumption	100-240VAC, 50-60Hz (universal) 384 watts (typ)
CONTROLS	Physical OnView®	Standby, menu, input, reset, H/V keystone Language (English, French, Spanish, German, Italian, Russian, Swedish, Finnish, Portuguese, Simplified Chinese and Traditional Chinese), brightness, contrast, frequency, phase, sharpness, zoom, keystone, V. position, H. position, colour temperature, display format, audio (volume, treble, bass, stereo/mono, mute)
OPERATING CONDITIONS	Temperature Humidity	5-35°C 10-85% (non-condensing)
NOISE LEVEL	Normal Whisper Mode ¹	33dB (typ) 30dB (typ)
DIMENSIONS	Physical	330mm (W) x 100mm (H) x 269mm (D)
WEIGHT		3.4kg
REGULATIONS		TÜV/GS, CE B, UL/C-UL, FCC B, CB, CCC, VCCI
OTHER		Soft carrying case, remote with mouse control and laser pointer, picture-in-picture selectable display modes (PC/movie/game/sRGB/dynamic/user)
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

Optional Accessories

- Rolling soft case and laptop bag PRJ-SCA-001
- Replacement lamp RLC-002
- Universal ceiling mount kit WMK-005



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®



ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 02 5832 0356
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ The warranty for all ViewSonic LCD and DLP projectors (except PJ250) from 1 April 2004 is valid for three years, and includes an on-site exchange service during this period in all current European Union (France, Belgium, Netherlands, Luxembourg, United Kingdom, Ireland, Sweden, Denmark, Finland, Germany, Austria, Greece, Italy, Spain, Portugal) and EFTA countries (Switzerland, Liechtenstein, Norway, Iceland).
² Running whisper-mode exclusively can extend lamp life up to 4000 hours. ³ Optional cables required. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. PJ755D 12/04-UK

For more product information, visit us on the web at ViewSonicEurope.com