3M™ Digital Projector X65



- A great blend of features and performance!
- Powerful, bright performance.
- Ideal for medium sized rooms.
- Wide variety of computer and video connectivity.



COMPUTER **VIDEO BASIC SPECS** • RGB (x2 input, x1 output) • Component Video • 2500 lumens • USB mouse emulation • S-Video XGA (1024x768) • Computer (DVI-D x1) • RCA Composite • 9.9 lbs / 4.5 kg Audio (x2 input, x1 output) • RCA Audio (L,R) • 350:1 Contrast ratio Serial Control Horizontal and Vertical Digital keystone Component Video Input RCA Video Computer Input (2) Computer S-video HDTV readv Input (DVI-D/Digital RGB) (DVD,etc.) Input Input (RGB) Whisper mode increases lamp life of up to a total of 4000 hours - | 22122222 X65 Order Number: 78-9236-6821-0 Audio Input Monitor Output Serial Control USB Audio Input Output mouse emulation (Stereo mini) (Stereo mini)







1-800-328-1371 www.3m.com/meetings



3M™ Digital Projector X65



OPTICAL

- · Brightness: typical: 2500 lumens (2000 whisper mode)
- Imager set: 0.9" Polysilicon LCD
- Resolution (native): XGA (1024x768 pixels)
- Resolution (maximum): SXGA (1280x1024 pixels)
- Aspect ratio: 4:3 native, 16:9
- Colors: 16.7 million
- Screen size (range): 30-300 inches
- Zoom / Focus: Manual
- Zoom ratio: 1.3:1
- Projection lens: F (focal length): (1.7-2.1) (f =36.8-47.8 mm)
- · Optional lenses: No
- Contrast ratio (peak): 350:1
- Lamp: W, Type: 250w UHB
- Lamp life (average): 2000 (whisper mode): up to 4000 hours

ELECTRICAL

- Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- HDTV: 480i, 480p, 525i, 525p, 720p, 1080i
- Keystone Correction: Horizontal: ±5° Vertical: ±15°
- Audio: 2 x 1w
- Startup Screen: Customizable
- Picture in picture: Yes
- Noise level: normal (whisper): 40 (36) dB
- Feature set: Auto off, 4x digital magnification, blank, mouse emulation
- · Horizontal scan: 31-80 kHz
- Vertical scan: 56-120 Hz
- Power consumption: 410w
- Power supply: Universal: 90-132V / 198-264V (50/60 Hz)
- Regulatory approvals: UL, cUL, FCC Part 15 Class B, CE, TUV, EN60950
- Operating temperature: 32 95 F (0 35 C)
- Storage temperature: -4 140 F (-20 60 C)

SIZE

- Dimensions (W x H x D): 14.2 x 4.2 x 10.1in. (360 x 106 x 257 mm)
- Weight: 9.9 lbs / 4.5 kg

WARRANTIES

- Projector: 3 Years Standard
- Ultra Value Warranty available—includes free lamp and free loaner while unit is repaired and expedited service.
- Lamp: 1 Year Prorated

3M Visual Systems Division

Building A145-5N-01 6801 River Place Blvd. Austin, TX 78726-9000

3M Mexico, S.A. de C.V.

Apartado Postal 14-139 Mexico, D.F. 07070 Mexico

3M Canada

P.O. Box 5757 London, Ontario, Canada N6A 4T1

Litho in U.S.A. © 3M 2003

78-6970-8581-5

(09.03.15m)Printer

ACCESSORIES INCLUDED

- Power Cords (x3 US, UK, Euro)
- RGB computer cable
- Full function remote control
- RCA™ audio & video cable
- S-video cable
- · Component video cable
- Stereo mini audio cable
- Serial control cable
- Multilanguage Quick Start Guide
- Multilanguage Operator's Guide CD

OPTIONAL ACCESSORIES

- Ultra Value Warranty X65 (WX65) 78-6969-9707-7
- Lamp for X65 (EP8765LK) 78-6969-9547-7
- Ceiling Mount, (CM65) 78-6969-9696-2
- 26-47" Adjustable Extension for Ceiling Mount (HE200) 78-6969-9714-3
- Soft Side Case with Shoulder Strap Projector & Notebook Computer (EP7640CC) 78-6969-9203-7
- ATA Rolling Hard Shipping Case (EP1545) 78-6969-8925-6
- Soft Rolling Luggage Case (EP1555) 78-6969-8926-4

PROJECTION DISTANCE CHARTS — 3M X65				
Distance to Screen		Screen Size		
Minimum	Maximum	Diagonal	Width	Height
5.17ft.	6.83ft.	40in.	32in.	24in.
1.6m	2.1m	101.6cm	81.3cm	61.0cm
7.83ft.	10.25ft.	60in.	48in.	36in.
2.4m	3.1m	152.4cm	121.9cm	91.4cm
10.58ft.	13.67ft.	80in.	64in.	48in.
3.2m	4.2m	203.2cm	162.6cm	121.9cm
13.33ft.	17.08ft.	100in.	80in.	60in.
4.1m	5.2m	254.0cm	203.2cm	152.4cm
16ft.	20.5ft.	120in.	96in.	72in.
4.9m	6.2m	304.8cm	243.8cm	182.9cm
20.08ft.	25.67ft.	150in.	120in.	90in.
6.1m	7.8m	381.0cm	304.8cm	228.6cm
26.92ft.	34.25ft.	200in.	160in.	120in.
8.2m	10.4m	508.0cm	406.4cm	304.8cm

Note: These sizes are ± 10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of time specified on product packaging from the date of purchase (length of warranty period varies by region). 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.

1-800-328-1371

www.3m.com/meetings

