you can Canon

LV-7240

Product Specification

Projection System	Transmissive LCD panel x 3, Poly-silicon TFT Active Matrix
Number of Pixels	786432 (1024 x 768, XGA)
Horizontal Resolution	540 TV lines
Supported RGB input	UXGA (compressed) / SXGA (compressed) / XGA / SVGA / VGA
Zoom	1.2x, Manual
Focus	Manual
Projection Lens	F1.7 ~ F2.0; f=21.6 ~ 25.9mm
Contrast Ratio	300:1
Lamp	180W NSH
Screen Size	21" - 300"
Lens Shift	9:1
Image Elevation Adjustment	10° Maximum
Digital Keystone	Vertical Correction Range: +/- 30°, Automatic
Brightness	2100 Lumens (Quiet Mode: 1700 Lumens)
Uniformity	85%
Plug And Play	Supported
Digital Zoom	1x - 4x (16x Area Ratio)
Resolution	Native XGA
Input Terminals	Analogue RGB 1: Mini D-Sub 15-pin Analogue RGB 2: Mini D-Sub 15-pin S-Video: Mini DIN 4-pin Composite Video: RCA x 1 Audio: 3.5mm2 stereo mini-jack Audio: RCA x 2 (L/R) Audio: RCA x 2 (L/R) Projector Service and Control: Mini-DIN 8-pin
Output Terminals	Analogue RGB: Mini D-Sub 15-pin Audio: 3.5mm2 stereo mini-jack (variable level)
Progressive Scanning	Supported
AMSS (Automatic Scanning System)	Supported
Digital Gamma Correction	Supported
Picture Image Select	6 Modes: Standard, Presentation, Cinema, Video, sRGB, User
Speaker	1W RMS, Monaural
Video Compatibility	PAL / PAL-M / PAL-N / PAL-60 / NTSC / NTSC 4.43 / SECAM
Scanning Frequency	Horizontal Sync: 15 - 100kHz Vertical Sync: 50 - 120Hz Pixel Clock: 108MHz
Power Consumption	250W Max
Dimension (w x h x d)	294mm x 93mm x 260mm

Downloads
Brochures
Image Library
Throw Distance Calculator

Useful Info
Technology

3 Year Warranty
3 Year Extended Warranty

Weight	3.0kg

40"	1.2m
100"	3.0m
200"	6.0m
300"	9.0m

Parts and Labour	3 years
Lamp	90 days

© Copyright 2005 | Terms and Conditions of use

This document was created with Win2PDF available at http://www.daneprairie.com.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.