



**Model Name** Joybee GP3 Mini Projector

**Unique selling point**

- \* 300AL LED, 85% NTSC
- \* Wireless Streaming (PC/Mobile)
- \* 1.16 throw ratio (40" @ 1M)
- \* 2W stereo speakers x2 + SRS WOW HD
- \* Detachable battery
- \* Palm size with rich connectivity

**Trade Mark**




<b>Projection System</b>	DLP	
<b>Native Resolution</b>	WXGA(1280 x 800)	
<b>Brightness</b>	300AL	
<b>Contrast Ratio</b>	10000 : 1*	
<b>Display Color</b>	1.07 Billion Colors	
<b>Lens</b>	F=1.928 , f=26.95mm	
<b>Aspect Ratio</b>	Native 16:10 (5 aspect ratio selectable)	
<b>Throw Ratio</b>	1.16 (40" @ 1m)	
<b>Image Size (Diagonal)</b>	20"-160"	
<b>Zoom Ratio</b>	Fixed	
<b>Lamp Type</b>	OSRAM Q9	
<b>Lamp(Normal/Economic)*</b>	20,000/30,000 hours	
<b>Keystone Adjustment</b>	1D, Vertical +/- 40 degrees	
<b>Projection Offset</b>	100%±5%	
<b>Resolution Support</b>	VGA to VWSXGA+(1600X1050)	
<b>Horizontal Frequency</b>	31~99KHz	
<b>Vertical Scan Rate</b>	23~120Hz	
<b>Compatibility</b>	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	Video Compatibility	NTSC, PAL, SECAM
<b>Interface</b>	Computer in (D-sub 15pin)	x 1 (via CEA 30 pin cable)
	Composite Video in (RCA)	x 1 (via CEA 30 pin cable)
	Component Video in	N/A (share with D-Sub)
	HDMI (v1.3)	x 1 (mini type)
	Audio L/R in (RCA)	x 1 (via CEA 30 pin cable)
	Audio in	x 1 (mini jack)
	Audio out (Mini jack)	x 1
	iPod/iPhone Universal Dock	x 1 (w/ dock cover)
	Speaker	2W Stereo x 2 (w/ SRS WOW HD)
	USB (Type A)	x 1 (USB Drive/HDD/Wi-Fi dongle)
	USB (Type Mini B)	x 1 (USB Display/File transfer)
	Card Reader	x 1 (SD, SDHC up to 32GB)
	Internal memory	2GB (900MB for user usage)
<b>Dimensions (W x H x D)</b>	140.3 x 52.5 x 129.8 mm (without battery)	
	140.3 x 93.8 x 129.8 mm (with battery)	
<b>Weight</b>	0.56kg (1.23lbs) (without battery)	
	1.05kg (2.31lbs) (with battery)	
<b>Power</b>	Power Supply	AC 100 to 240 V, 50/60 Hz
	Power Consumption	45W/30W (Normal/eco), Standby<0.5W
<b>Audible Noise</b>	33/28 dBA (Normal/Eco)	
<b>On-Screen Display Languages</b>	Arabic / Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Hindi / Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai / Traditional Chinese (28 Languages)	
<b>Picture Modes</b>	Bright/Standard/Cinema/Game/User	
<b>Accessories</b>	<b>Standard</b>	<b>Optional</b>
	Remote Control w/ Battery	Battery P/N : 5JJ3C01.001
	Carry Bag	(1) 2.5 hrs battery life @ 150AL (1hr @ 300AL)
	Adapter (by region)	(2) Battery life time : 300 cycles charging
	USB Cable	(3) Charging time : 3.5 hrs in empty condition
	Power code	
	User Manual CD (24L)	
	Quick Start Guide	
	Warranty Card (by region)	
	Mini HDMI adaptor	
	CEA 30 Pin Cable	
	Wi-Fi dongle	
<b>Multimedia Support Format</b>	<b>Video</b>	AVI (H.263, Xvid, MJPEG), MOV (H.263, Xvid, MJPEG), MP4 (H.263, Xvid), 3gp/3g2 (H.263, Xvid), FLV (Sorenson Spark) (Please visit BenQ.com to know more details about the latest supported formats.)
	<b>Music</b>	MP3, MP2, APE, FLAC, OGG, WAV , M4A
	<b>Photo</b>	JPG (.jpg/.jpeg) , BMP (.bmp) , PNG (.png)
	<b>Subtitle</b>	MKV build-in, SRT (.srt)
	<b>Document</b>	Adobe PDF 1.0-1.4 (.pdf), MS PowerPoint 97-2010 (.ppt, .pptx), MS Excel 95-2010 (.xls, .xlsx), MS Word 95-2010 (.doc, .docx), Text (.txt)
<b>USB Display</b>	<b>System Requirements</b>	CPU Intel/AMD Dual Core 2 GHz or higher (ATOM not supported)
		Graphic card nVIDIA or ATI graphic card with 64MB VRAM or above
		OS Windows XP Professional SP2, Vista SP2, Windows 7 SP1, windows8 (32 and 64-bit)
		A/V sync Support both of image and audio streaming
<b>Wireless Display for Windows (GP3 EZ QPresenter)</b>	<b>System Requirements</b>	CPU Dual Core 1.8 GHz or better (excluding atom processor)
		Graphic card nVIDIA or ATI graphic card with 64MB VRAM or above
		OS Windows XP SP2/SP3 (32 and 64-bit) / Vista (32 and 64-bit) / Windows 7 (32 and 64-bit) / Windows 8 (32 and 64-bit)
		Wi-Fi 802.11n
		A/V sync Support both of image and audio streaming
<b>Wireless Display for MAC (GP3 EZ QPresenter)</b>	<b>System Requirements</b>	CPU Intel Dual Core 1.4 GHz or better (PowerPC not supported)
		Graphic card nVIDIA or ATI graphic card with 64MB VRAM or above
		OS Mac OS X 10.5 and above
		Recommended Models MacBook after 2009-01-21 All series of MacBook Pro MacBook Air after 2010-06-08
		Wi-Fi 802.11n
		A/V sync Support both of image and audio streaming

\*10000:1 is under the condition that background illumination <=0.02 lux

\*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

Distance Chart



1280:800 screen diagonal			Recommended projection distance from screen in mm
Feet	Inches	mm	Average
2.00	24	610	621
3.33	40	1016	1034
4.67	56	1422	1448
6.00	72	1829	1862
6.66	80	2032	2069

All measurements are approximate and may vary from the actual sizes. BenQ recommends that if you intend to permanently install the projector, you should physically test the projection size and distance using the actual projector in situ before you permanently install it, so as to make allowance for this projector's optical characteristics. This will help you determine the exact mounting position so that it best suits your installation location.

Dimension

