

The EB-G6270W is a professional installation projector ideal for corporate environments, education applications, rental markets and digital signage. Important presentations and sales campaigns are delivered with rich, vivid colours - even in daylight, thanks to Epson's 3LCD technology and equally high White and Colour Light Output. The projector can even be placed in difficult positions thanks to a number of innovative installation features.

Ensure superb quality and the best possible delivery of presentations with the EB-G6270W. This 6,500-lumen projector includes Epson's 3LCD technology and high brightness to display images with more accurate colours and clearer detail. A new enhanced standard lens helps reduce flare and improve focus.

Set-up and installation is simple and straightforward. A wide lens shift allows easy placement of the projector, even in difficult positions, without distorting or blurring the image. In addition, a powerful zoom lens, as well as manual vertical keystone correction and centred lens, make it even easier to set-up in various positions. The projector can also be rotated vertically by 360 degrees allowing images to be projected directly onto the ceiling and the floor<sup>1</sup>.



# **KEY FEATURES**

• Ultra-bright output Equally high 6,500lm White and Colour Light Output

- High-quality image 3LCD technology, WCLO, colour uniformity, enhanced standard lens
- Flexible installation Wide lens shift, manual vertical keystone correction
- Easy to set up HDBaseT and HDMI connectivity. Compatible with Epson EB-G5 series lenses<sup>2</sup>



**EXCEED YOUR VISION** 

# PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology, RGB liquid crystal shutter	
LCD Panel	0.76 inch with C2 Fine	
Colour Light Output	6,500 lumen-4,550 lumen (economy)	
White Light Output	6,500 lumen - 4,550 lumen (economy)	
Resolution	WXGA, 1280 x 800, 16:10	
Contrast Ratio	5,000 : 1	
Lamp Kauntana Composition	380 W, 2,000 h durability, 4,000 h durability (economy mode)	
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °	
High Definition	HD ready	
Aspect Ratio	16:10 10 Bits	
Colour Processing		
OPTICAL		
Projection Ratio	1.26 - 2.30:1	
Zoom	Manual, Factor: 1 - 1.8	
Projection Size	50 inches - 300 inches	
Projection Distance Wide	1.4 m - 8.4 m	
Projection Distance Tele	2.5 m - 15 m	
Projection Lens F Number	1.65 - 2.55	
Focal Distance	21.28 mm - 37.94 mm	
Focus	Manual	
Projection Lens Zoom Ratio	1 - 1.8 : 1	
Lens	Optical	
Lens Shift	Manual - Vertical ± 67 %, horizontal ± 30 %	
CONNECTIVITY		
Interfaces	HDBaseT, Cinch audio in, RS-232C, Stereo mini jack audio in (4x), Stereo mini jack audio out,	
	S-Video in, BNC in, Composite in, Display Port, HDMI in, VGA out, VGA in, Wireless LAN IEEE	
	802.11b/g/n (optional), WLAN, 10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T)	
ADVANCED FEATURES		
	Kanaington look Doopword look	
Security Features	Kensington lock, Password lock Mute key, Network administration, Network image transmission, PC Free Quick Corner, Six	
i caldies	Mute key, Network administration, Network image transmission, PC Free, Quick Corner, Six	
Video Colour Modes	axis color control, Split-Screen-Function, Transport handle	
	Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM	
	Auto, Dynamic, Living room, Natural, Cinema	
2D Colour Modes GENERAL	Auto, Dynamic, Living room, Natural, Cinema	
2D Colour Modes GENERAL Energy Use		
2D Colour Modes GENERAL Energy Use	Auto, Dynamic, Living room, Natural, Cinema	
2D Colour Modes GENERAL Energy Use Product dimensions	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby)	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A)	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A)	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% MB22 ceiling mount	
2D Colour Modes 2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity Options Sound Pressure	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity Options Sound Pressure	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% MB22 ceiling mount	
2D Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity Options	Auto, Dynamic, Living room, Natural, Cinema 542 W, 405 W (economy), 0.41 W (standby) 505 x 406 x 171 mm (Width x Depth x Height) 9.9 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Monitor, EasyMP Multi PC Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% MB22 ceiling mount	

### EB-G6270W

## WHAT'S IN THE BOX

- Cable hook
- User manual (CD)
- Remote control incl. batteries
- Power cable
- Computer cable
- Cable cover

1. - Requires additional ceiling mount 2 - Except ELPLS05 lens

**EPSON**<sup>®</sup>

## **OPTIONAL ACCESSORIES**

- 3D Polarizer ELPPL01 V12H618A01
- Air Filter ELPAF43
   V13H134A43
- Lamp ELPLP76
- V13H010L76
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Wireless LAN Adapter (b/g/n) ELPAP07 V12H418P13
- Ceiling Mount (White) ELPMB22 V12H003B22

## **OPTIONAL LENSES**

- Lens (ST Off Axis) ELPLU01 V12H004U01
- Lens (Long Throw) ELPLL06 V12H004L06
- Lens (Middle Throw 2) ELPLM05 V12H004M05
- Lens (Middle Throw 1) ELPLM04 V12H004M04
- Lens (Rear Wide) ELPLR03 V12H004R03

#### LOGISTICS INFORMATION

SKU	V11H702041 V11H702040
EAN code	8715946548579
Dimensions Single Carton	762 x 432 x 324 mm
Carton Weight	12.9 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	7 Units



\* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece 210-8099499 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429

South Africa (+2711) 465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

