

EP738

Bright, Quiet and so Versatile

The EP738 mobile projector, designed for ease of use and versatility. With auto set-up and built in memory modes, it is easy to achieve the best quality display in any application, be it in boardrooms, in schools or movies at home. The brilliant images speak for themselves yet the projector cannot be heard thanks to the near-silent cooling system.



- Brightness of **1700 lumens**, for presentations in any environment
- Exceptionally **Quiet 27dB** for unobtrusive operation
- Superior **Contrast of 2000:1** for unparalleled image clarity
- **Auto set-up and Custom memory modes** - PC, Movie, Game, sRGB and User
- **Optical zoom** for maximum flexibility
- **Ultra portable lightweight**, only **2.4kg**
- **sRGB** for accurate colour matching

Specifications

Resolution	Native: SVGA 800 x 600 up to 1280 x 1024 SXGA compressed		
Brightness	1700 ANSI Lumens	Power Supply	100-240v, 50-60 Hz
Contrast Ratio	2000:1	Power Consumption	265W Maximum, Standby <15w
Noise Level	27dB (ECO Mode)	Dimensions (W x H x D)	265 x 104 x 236mm (W x H x D)
Lamp Life	3000 hours (ECO mode)	INPUTS:	
Lamp Type	200 watt SHP	PC RGB (RGB SCART)	15 Pin D-Sub VGA (SCART RGB Adaptor option)
Video Compatibility	PAL , SECAM 625/576i\p NTSC 525/480i\p HD 720p/1080i	Analogue Component	15 Pin D-Sub VGA (component adaptor option)
Aspect Ratio	4:3/16:9 compatible	S-Video	4 Pin Mini Din
Projection Types	Front, Ceiling mounted, Rear, Rear ceiling mounted	Composite	RCA Jack
Throw Ratio	2.0 ~ 2.4:1 (Projection Distance:Image Width)	Stereo Audio	Mini Jack
Projection Distance	1.2m -10.0m (3.94' - 32.8')	Serial Contol	RS232 Mini-DIN
Image Size	0.63m - 5.21m (27.6" to 267.2") Diagonal 4:3	OSD Languages	11 Languages including: English, German, Italian, French, Spanish, Norwegian and Russian
Keystone correction	± 16 degrees Vertical		
Remote Control	Infra-Red with PC page up/down function via USB		
Projection Lens	f=22.3 ~ 26.8mm, F/2.6 ~ 2.81, Manual Focus		
Weight	2.4 Kg		
Uniformity	85%		

OptomaEurope

