

Specifications

Model name	LSPX-W15
Projection unit	
Display system	Projection system
Display device	SXRD 0.74" x 3
	Number of pixels
	4096 x 2160 x 3 pixels
Projection lens	Zoom
	Focus
	Corner correction adjustment
Projection image size	66" to 147"
Light source	Laser diode
Light output	[lm]
	2,000 lm
Color light output	[lm]
	2,000 lm
Accepted digital signals*	VGA, SVGA, XGA, WXGA(1280x768), Quad-VGA, SXGA, SXGA+, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p, 1080/24p, 3840x2160/24p, 3840x2160/25p, 3840x2160/30p, 3840x2160/50p**, 3840x2160/60p**, 4096x2160/24p, 4096x2160/25p, 4096x2160/30p, 4096x2160/50p**, 4096 x 2160/60p**
Audio	Power output
	40W + 40W (at 8 Ω)
	Supported format
	LPCM 2CH (up to 48kHz)
	Frequency response
	40Hz - 20kHz
Inputs/Outputs (Video/Audio/Control)	HDMI inputs
	4
	Speaker terminals
	2
	REMOTE
	RS-232C, D-sub 9-pin
	LAN
	RJ45, 10BASE-T/100BASE-TX
	IR IN
	Mini Jack
	USB
	TypeA, DC 5 V, Max. 500 mA
Operating temperature / Operating humidity	41°F to 95°F (5°C to 35°C) / 35% to 85% (no condensation)
Storage temperature / Storage humidity	-4°F to +140°F (-20°C to +60°C) / 10% to 90% (no condensation)
Power requirements	AC100V to 240V, 50/60Hz
Power consumption	520W
Standby mode power consumption	0.5W
Exterior material	Aluminum / Steel
Dimensions (WxHxD)	43 3/8 x 10 1/2 x 21 1/8 inches (1100 x 265 x 535mm)
Mass	Approx. 113lb 8.6oz (51.5kg)
Features	Picture Position Memory / Reality Creation / TRILUMINOS™ display / 3D Format Support with RF 3D Transmitter
Supplied accessories	Remote control (1) / Size AA (R6) manganese batteries (2) / AC power cord (1) / Plug holder (1) / Bottom cover (front, large) (1) / Bottom cover (front, small) (1) / Bottom cover (side) (2) / Terminal door (1) / Adjustment tool (1) / Operating Instructions (1) / Warranty card (1)
Optional accessories	Active 3D Glasses
	TDG-BT500A

*60p,30p,24p include 59.94/60Hz, 29.97Hz/30Hz, 23.98Hz/24Hz **YCbCr 4:2:0 / 8bit format signal

Speaker unit

Speaker system	Passive 2 way speaker system
Woofers	5 1/8 inches (130mm), cone type x1
Tweeter	3/4 inches (19mm), dome type x1
Enclosure type	Bass reflex
Rated impedance	8Ω
Exterior material	Aluminum / Wood
Dimensions (WxHxD)	7 7/8 x 10 1/2 x 21 1/8 inches (200 x 265 x 535mm)
Mass	Approx. 21lb. 6.2oz (9.7kg)
Supplied accessories	Speaker cords (2) / Operating Instructions (1)

Cabinet unit

Exterior material	Aluminum / Wood
Load capacity	Top board
	22lb 0.7oz (10kg)
	Middle shelf
	15lb 6.9oz (7kg)
	Bottom shelf
	55lb 1.8oz (25kg)
External dimensions (WxHxD)	23 5/8 x 10 1/2 x 21 1/8 inches (600 x 265 x 535mm)
Inner dimensions (WxHxD)	22 5/8 x 7 1/2 x 19 5/8 inches (573 x 190 x 496mm)
Mass	Approx. 47lb 6.4oz (21.5kg)
Supplied accessories	Operating Instructions (1)

	Projection image size (Diagonal)		Placement distance	
	Maximum	Minimum	Wall to rear of the unit	Wall to front of the unit
Case of maximum image size	147"	92"	7inch (17cm)	28inch (70.5cm)
Case of minimum distance	106"	66"	0inch (0cm)	21inch (53.5cm)

Dimensions

