



Specifications

Display Technology:	0.55" Double Data Rate DLP™ Technology Texas Instruments
Resolution:	Native SVGA (800 x 600)
Brightness (Typical):	1500 Lumens
Contrast Ratio	2000:1
Audible Noise	TBC
Aspect Ratio:	4:3 Native, 16:9 Compatible
Weight:	2 kg
Computer Compatibility:	H Sync. 31.5 – 100 kHz, V Sync 56 – 85 Hz
Video Compatibility:	PAL (B, D, G, H, I, M, N), NTSC (M, 4.43/3.58 MHz), SECAM (B, D, G, K, K1, L) 480i/p, 576 i/p, HDTV (1080i & 720p)
Uniformity	85%
Projection Lens:	F / 2.7 ~ 3, f = 22 ~ 24 mm, 1:1.1 Manual Focus
Throw Ratio:	1.9 - 2.1 : 1
Zoom Type	1:1.1 x Manual Zoom
Projection Distance	1.5 ~ 10 meters
Image size	0.88 – 6.46m (Diagonal 4:3)
Keystone Correction:	±15 degree Vertical
Projection types	Front, Front ceiling mounted, Rear, Rear ceiling mounted
Lamp Type:	160 W User Replaceable SHP Lamp
Lamp Life:	3,000/5,000 Hours Std/ECO
Dimensions: (W x D x H)	230 x 95 x 230 mm
Power Supply:	100 - 240 V, 50 - 60 Hz with PFC Power Supply
Power Consumption:	360 W. Standby mode < 20 watts
Operating Conditions:	5 ~ 35°C, Max. humidity 80%, Max. altitude 3000m

INPUTS

PC 1 RGB (RGB SCART/HDTV)	15 Pin D-Sub VGA
PC 2 RGB	15 Pin D-Sub VGA
S-Video	4 pin Mini DIN
Composite	RCA Jack
Stereo Audio	Mini Jack

OUTPUTS

PC RGB	15 Pin D-Sub, Monitor loop-through
Audio	1 x 2W

Security:	1 Kensington Lock Port / Password Protection at Start Up
------------------	--

Standard Accessories:	Lens Cover, AC Power Cord, VGA – VGA Cable, Composite Video Cable (RCA to RCA), Basic Infra Red Remote Control, AAA Type Batteries x 2, Quick Start Card, CD User Manual, Warranty Card
------------------------------	--

Optional Accessories:	Ceiling Mount Kit, Full Function Remote inc. Remote Mouse and USB cable, Soft Carry Case, VGA/SCART Adapter
------------------------------	---

www.optomaeurope.com

Optoma Europe Ltd, 42 Caxton Way, Watford Business Park, Watford, Herts WD18 8QZ UK.
+44 (0)1923 691 800 +44 (0)1923 691 888

