





The Big Picture

Up to a huge 8.38m diagonal image size, 2.78m image size from only 4m, 2.0m image size from only 3m.



Designed for European Widescreen Home Cinema the ThemeScene™ H30 Advanced presents breathtaking image quality, near silent operation and unrivalled ease of use.

True native widescreen, a bright 850 lumens of video optimised light output and 3000:1 contrast ratio gives sparkling, crystal clear images with fantastic detail.

Effortlessly connect to HDMI, DVI, Component Progressive and SCART RGB sources for the highest possible image quality from your DVD player, Digital TV box, Digital Recorder, High Definition system or Games Console.

Videophile Quality

Image quality previously available only from professional Digital Cinema Projectors. Enabled by ThemeScene™ expert engineering, DarkChip2™ DLP™, 3000:1 Contrast Ratio, 850 Lumens and a 6 segment, 4x colour wheel.

Whisper Quiet - Less than 26dB at 2 metres.

Digital Projection System

DLPTM technology is the only digital projection technology. The best Digital Cinemas around the world use DLPTM technology, that same technology is used in the H30 Advanced. With a digital HDMI or DVI signal you can create a true digital projection system that produces a spectacular Cinematic experience in your own home.

Ultimate Connectivity

You can connect your digital source (DVD or set-top box) directly to the DVI or HDMI input and still have a component progressive input free, for other high quality analogue sources.




Total Control

- Digital Lens shift with 2 positional memories
- No more black bars top and bottom with Multiple Quick Zoom Presets 1.85:1, 1.66:1, 2.35:1, 4:3 to 16:9
- Get the picture exactly right with 5 separate user adjustable memory settings
- Red Green and Blue Brightness and Contrast settings for image calibration
- Advanced High Definition scaling enhancement technology for superior HD reproduction
- Edge Mask to maintain 1:1 pixel mapping with NTSC interlaced sources

SCART RGB Adaptor

The unique SCART RGB adaptor supplied enables very high quality, inexpensive computer monitor VGA cables to be used to connect easily to your DVD player, Digital TV or games console. These cables can be up to 20m long making it easy and inexpensive to position the H30 Advanced exactly where you want it.



Flexible positioning

Getting a big image in your room has never been simpler. Easy to position anywhere, you can either place it on a coffee table or use the ½" camera tripod style fixing to attach to a floor or table top stand. The high image offset of the H30 Advanced enables ceiling mounting to be unobtrusively close to the ceiling whilst coffee table mounting can be close to the floor hidden underneath the main table surface.

"Colours look fabulously vibrant too, benefiting immensly from the H30A's extra brightness and contrast. Arguably even more impressive than their sheer richness."

John Archer - What Video & Widescreen



Technical Specifications

Highlights

Aspect Ratio Widescreen (16:9)

Contrast 3000:1

Audible Noise 26dB @ 2m Normal mode, 29dB @ 2m Brite™ mode

Brightness 850 Video Optimised Lumens

Connections

Video Inputs Connector Type

HDMI DVI-I via optional adaptor

DVI DVI-I

SCART RGB DVI-I via supplied adaptor

Component I/P I. 3 x RCA

2. DVI-I via supplied adaptor

S-Video Mini DIN Composite Video RCA

Computer DVI-D DVI-I

VGA 15 Pin D-Sub DVI-I via supplied adaptor

Video Compatibility PAL, SECAM (576i/p), NTSC (480i/p), HDTV (1080i, 720p)

Display

Display Technology 0.54" DarkChip2™ (Native 854 x 480) Colour Wheel 4 x speed 6 Segment (RGBRGB)

Throw Ratio 1.65-2.0 (Projection Distance/Image Width) Manual zoom

Projection Distance 1.4m – 12m

Image Size 0.81m to 8.38m (16:9 Diagonal)

Keystone Correction Vertical ± 16 degrees

Projection Types Front, Ceiling, Rear, Rear ceiling

Lamp Type 200 watt P-VIP

Lamp Life Normal mode 3000 hours

General

Dimensions $272 \text{mm} \times 210 \text{mm} \times 86 \text{mm} \text{W} \times \text{D} \times \text{H}$

Weight 2.2 kg

Power Consumption 270W Max, 5 watts standby Operating Temperature 10 - 40°C Max, 80% Humidity

Mounting Ceiling mount points and ¼' screw mount for camera style tripod

Warranty Three (3) years limited warranty 90 days for lamp
Menu Languages 10 Languages including: English, French, German, Italian,

Spanish, Portuguese and Russian


Supplied accessories AC power cord, Composite video cable, S-video cable

 $3 \times$ RCA component to DVI-I adaptor, VGA 15 Pin D-Sub to DVI-I adaptor, SCART RGB to VGA 15 Pin D-Sub adaptor, Remote control with backlight

Batteries for Remote control, Lens cap, Users guide, RS-232 Cable

Optional accessories Ceiling Mount Kit, HDMI to DVI adaptor


ThemeScene ** is a registered trademark of Optoma Europe Ltd. All other product names and company names used herein are for identifications purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. Digital Upit Processing, DLP and the DLP medialion are trademarks of Flexa Instruments.



*SCART RGB & Component I/P (via supplied adapter)
HDMI (via optional adapter)

H30 Advanced Projection Distance/Image Size					
Projection Distance(m)	Max. Diagonal Image Size(m)	Min. Horizontal Image Width(m)	Max. Horizontal Image Width(m)	Min. Image Offset(m)	Max. Image Offset(m)
2.00	1.39	1.00	1.21	0.23	0.27
3.00	2.08	1.50	1.82	0.34	0.41
4.00	2.79	2.00	2.42	0.45	0.55
5.00	3.48	2.50	3.03	0.58	0.68
6.00	4.16	3.00	3.64	0.68	0.82
7.00	4.88	3.50	4.24	0.79	0.96
8.00	5.56	4.00	4.85	0.90	1.10
9.00	6.25	4.50	5.45	1.02	1.23
10.00	6.96	5.00	6.06	1.13	1.37

For guide purposes only





(UK Only) In the unlikely event of your projector requiring attention within 3 years of purchase, we will collect it on a next day collection service, repair and then returned to you. If you require a projector during the repair we will loan you a replacement unit.*

*The loan unit may not be the same model or have the same features as the unit being repaired. The Total Care warranty applies to the UK mainland only.







Optoma Europe Ltd

42 Caxton Way Watford Business Park Watford, Hertfordshire, UK, WD 18 8 OZ

For your local reseller please contact:

Tel: +44 (0) | 923 69 | 800 Fax: +44 (0) | 923 69 | 888 www.themescene.tv