

ddv 2100

Always to hand

Liesegang
projection technology



ddv 2100 - Always to hand

Liesegang presents its new portable business projector, the **ddv 2100**. Due to its low weight, the XGA projector is ideal for mobile use or for room-to-room presentations. It is suitable for daylight projection with a brightness of 2,100 ANSI lumens. In addition to its high quality, the **ddv 2100** is convincing with its excellent video playback and constant colour presentation.

- XGA resolution
- 2,100 ANSI lumens
- Contrast ratio 2,000:1
- Weight 2.2 kg
- For mobile use
- Whitepeaking

ddv 2100



ddv 2100

Always to hand



- Accurate image presentation in "real mode"
- Individually adjustable colour management
- Four preset gamma correction values
- User-friendly menu

Liesegang ddv 2100

1213 0000 0000

including power cord, connecting cable
remote control, user manual, transportation bag

EAN 4044714211327

Accessories

- 200W UHB Lamp ZU 1213 04 4010
- Ceiling mount universal ZU 0260 75 0010
- Travelcase midi ZU 0298 98 0010

Technical Data*		ddv 2100
Technology		1 x 0,55" DLP™
Native Resolution		XGA, 1,024 x 768 Pixel
Supported Resolution		UXGA, 1,600 x 1,200 Pixel
Video Compatibility		PAL, SECAM, NTSC, HDTV
Contrast Ratio		2,000:1
Brightness Standard Mode		2,100 ANSI lumens
Brightness Whisper Mode		1,600 ANSI lumens
Lamp, Lifetime**		200 W UHB, 2,000 h
Mains Voltage		100 - 120 / 220 - 240 VAC, 50-60 Hz
Power Consumption		250 W / < 10 W Stand-by
Dimensions (D x W x H)		256 x 200 x 88 mm
Weight		2.2 kg
Keystone Correction		± 15° vert.
Scanning Frequency hor./vert.		15 - 79 kHz / 50 - 85 Hz
Pixel Clock		100 MHz
Image Uniformity		>80%
Speaker		1 x 2 W
Projection Lens		f=18.0 - 21.5 mm 1,2 x manual zoom
Digital Zoom		1.2 - 10 m
Projection Distance		0.77 - 7.70 m
Screen Size (diagonal)		1.6 - 1.93
Throw ratio		33 dB Standard Mode 29 dB Whisper Mode
Noise level		
Connectors		
Computer in		1 x RGB analog (D-Sub HD)
Video in		1 x Video (Cinch) 1 x S-Video (Mini-DIN) 1 x Component (RGB-analog)
Audio in		1 x Audio Stereo (mini jack)
Approvals		CE, FCC-B, UL
Miscellaneous Specifications		
		• automatical signal detection • multilingual On-Screen Menu

* Subject to modification ** average life time

Distance in	Image Size in				Image Diagonal in				
	m	inch	from	to	m	inch	from	to	
1.5	59.1	0.78	0.94	30.6	36.9	0.97	1.17	38.3	46.2
2.0	78.7	1.04	1.25	40.8	49.2	1.30	1.56	51.0	61.5
2.5	98.4	1.30	1.56	51.0	61.5	1.63	1.95	63.7	76.9
3.0	118.1	1.55	1.88	61.2	73.8	1.94	2.35	76.5	92.3
5.0	196.9	2.59	3.12	102	123	3.24	3.90	127.5	153
7.0	275.6	3.63	4.38	142.8	172.3	4.54	5.47	178.5	215

Liesegang Optoelectronics GmbH
Vogelsanger Weg 91
D-40470 Duesseldorf
Germany
phone +49 (0)211/3901-1
fax +49 (0)211/3901-227
www.liesegang.com
info@liesegang.com

Yours Liesegang Partner