PJ406D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Brilliant portability.

The ViewSonic® PJ406D DLP™ projector delivers brilliant, high-contrast images in an ultra-portable 4.5 pound package. This tiny powerhouse is LOADED WITH FEATURES ONLY FOUND ON MORE EXPENSIVE MODELS; like crisp, clear images with 1,900 lumens, 800x600 native resolution scalable to 1280x1024 and advanced video features like motion adaptive 3:2 pull down delivering smoother video performance. PERFECT IMAGES ARE GUARANTEED IN VIRTUALLY ANY SETTING by the optical zoom lens and digital keystone correction. Bring it with you to important business presentations or home for family movie night with the included soft carrying case. The PJ406D is the perfect choice for users looking for an easy-to-use, portable projector that won't break the bank.

It's not just another portable projector. It's a ViewSonic.

A TEXAS INSTRUMENTS TECHNOLOGY

BRILLIANT PRESENTATIONS ANYWHERE

- > Bright in virtually any setting with 1,900 lumens
 Packs 1,900 lumens in just 4.5 lb. It's the bright choice
 for mobile presenters.
- > Ultimate video source flexibility

 Connect a computer or add a video source for dynamic meetings and presentations.
- Supports HD signals including 720p and 1080i Capable of displaying HDTV signals as well as other video and data sources*.
- Advanced video features Motion adaptive deinterlacer for superior video performance.
- > Whisper-mode extends lamp life
 Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > OnView® controls for superior screen adjustablility Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.
- > The best warranty
 in the business
 Covered by a three-year
 parts and labor limited
 warranty, first-year Express
 Exchange® and one-year
 lamp warranty.***



PJ406D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION





PJ406D Distance Calculator				
Image Size (Diagonal in.)	Height (in.)	Width (in.)	Throw Distance (in.)	
35	28	54	60	
60	48	93	102	
80	64	124	136	
100	80	154	170	
120	96	185	205	
150	120	232	256	
200	160	309	341	
254	203	392	433	

Throw ratio: 1.8:1 (distance:width)
Accuracy of the calculations are +/- 5%
For additional calculations visit ViewSonic.com

Optional Accessories

• Replacement lamp
• Hard case with wheels
• Extended Express Exchange®PRJ-EE-05-03
• Soft case with wheels and laptop bag
• Universal ceiling mount kit WMK-005

PROJECTOR	Туре	0.55" DDR DMD, (DLP™)	
	Pixel Format	800x600 SVGA	
	Lens	Manual zoom/manual focus	
	Zoom Factor	1.1	
	Keystone	Vertical ± 15°	
DISPLAY	Size	35"-254" (diagonally)	
	Throw Distance	59"-393"	
	Throw Ratio	1.93–2.13:1	
	Lamp	200W, 2,000 hours**	
	Brightness	1,900 lumens	
	Contrast Ratio	2000:1	
	Aspect Ratio	4:3 (native), 16:9	
AUDIO	Speakers	1x2 watts	
INPUT SIGNAL		NTSC M, NTSC 4.43, PAL, SECAM, HDTV	
IN OI SIGNAL	Computer and video	(480i, 480p, 576i, 576p, 720p, 1080i)	
	Eroguanav	F _h : 31.5–80kHz; F _v : 56–85Hz	
COMPATIBILITY	Frequency PC	Analog: from VGA up to UXGA (scaled)	
	Mac®†		
		Analog: up to SXGA (may require a Mac adapter)	
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)	
	RGB (output)	15-pin HD, D-sub cable (x1)	
	Composite Video (input)	RCA jack (x1)	
	S-Video (input)	Mini-Din 4-pin (x1)	
	Component Video (input)	VGA DB-15 to HDTV/component cable*	
	Audio (input)	Stereo mini-jack (x1); RCA (L/R)	
POWER	Voltage	100–240 VAC, 50/60Hz (universal)	
	Consumption	250W (typ)	
CONTROLS	Basic	Standby/On, input, menu	
	OnView [®]	Images I (display mode, brightness, contrast, white intensity,	
		color temperature, sharpness), images II (frequency, phase,	
		H. position, V. position, degamma, aspect ratio, V. shift 16:9)	
		color setting, language, management (projection, keystone,	
		reset), lamp setting (lamp hour, lamp reset, whisper mode)	
OPERATING	Temperature	41–95°F (5–35°C)	
CONDITIONS	Humidity	10–85% (non condensing)	
NOISE LEVEL	Normal/Whisper mode	37 dB (typ); 30 dB (typ)	
DIMENSIONS	Physical (mm)	237.5mm x 96.5mm x 210.5mm	
(W x H x D)	Physical (in.)	9.4" x 3.8" x 8.3"	
WEIGHT	Net	4.5 lb. (2.1 kg)	
	Gross	8.2 lb. (3.7 kg)	
REGULATIONS		UL, C-UL, FCC-B, TUV/GS, CCC, CB, CE, GOST, NOM, PSB	
OTHER		Vertical digital keystone correction, progressive scan,	
		3:2 pull down, whisper mode	
PACKAGE CONTENTS		Projector, power cords, VGA cable, RCA video cable,	
		remote control, soft case, lens cap, ViewSonic Wizard CD,	
		Quick Start Guide	
WARRANTY		Three-year limited warranty on parts and labor, first-year	
· · · · · · · · · · · · · · · · · · ·		Express Exchange® Service. One-year warranty on lamp***	
		Express Exchange Service. One-year warranty on lamp	



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967• Fax (909) 839-7922• SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life up to 3,000 hours. ***Three-year limited warranty and 1-year lamp warranty available in U.S. and Canada for current projector models purchased on or after May 1, 2002. Applies to manufacturer's original installed lamp only. All accessory lamps purchased separately are warranted for 90 days. Subject to terms and conditions, verification and approval. For Express Exchange program details, visit ViewSonic.com. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12612-008-09/05] PJ406D-1