PJ458D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Bright DLP™ projector

ViewSonic's PJ458D projector features DLP™ technology to display digitally sharp images. WITH 2,000 LUMENS IN JUST 4.9 POUNDS this powerful little projector is ideal for classrooms and board rooms, on the road or in your home. The native 1024x768 XGA resolution, DIGITAL KEYSTONE CORRECTION AND ZOOM LENS ENSURE THAT YOU WILL GET THE BEST POSSIBLE IMAGE for whatever the setting. Advanced video features deliver smooth full-motion video while multiple inputs allow you to connect several display sources at once so you can give dynamic presentations. Whisper mode extends your lamp life further improving the PJ458D's overall value.



PERFORMANCE AND RELIABILITY

- > Bright in virtually any setting with 2,000 lumens Packs 2,000 lumens in just 4.9 lb. It's the bright choice for mobile presenters.
- > DLP™ Technology

 Stunning all digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- Ultimate video source flexibility Connect a computer or add a video source for dynamic meetings and presentations.
- > Supports HD signals including 720p and 1080i Capable of displaying HDTV signals as well as other video and data sources*.
- Advanced video features Motion adaptive deinterlacer for superior video performance.
- Whisper-mode extends lamp life Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > OnView® controls for superior screen adjustablility Screen geometry and color adjustments are precisely

made via an easy-to-use, on-screen menu.

> The best warranty
in the business
Covered by a three-year parts
and labor limited

and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***





PJ458D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION







Optional Accessories

• Replacement lamp	RLC-014
• Hard case with wheels	PRJ-HCA-001
• Extended Express Exchange®	PRJ-EE-05-03
Soft case with wheels and laptop bag	PRJ-SCA-004
• Universal ceiling mount kit	WMK-005
• VGA to component video adapter	ADPT-002

PROJECTOR	Tura	0.55" DDR DMD, DLP™
PROJECTOR	Type Pixel Format	1024×768 XGA
	Lens	Manual zoom/manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	31.2"–312" (diagonally)
DISFLAT	Throw Distance	46.8"–393.6"
	Throw Patio	1.57–1.89:1
	Lamp	200W, 2,000 hours**
	Brightness	2,000 ANSI lumens
	Contrast Ratio	2,000 ANSI lumens 2000:1
AUDIO	Aspect Ratio	4:3 (native), 16:9
AUDIO INPUT SIGNAL	Speakers	1x2 watts
INPUT SIGNAL	Computer and Video	NTSC M, NTSC 4.43, PAL, SECAM, HDTV
		(480i, 480p, 576i, 576p, 720p, 1080i)
COMPATIBILITY	Frequency	F _h : 31–79kHz; F _v : 50–85Hz
COMPATIBILITY		Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input)	Stereo mini-jack (x1); RCA (L/R)
POWER	Voltage	100–240 VAC, 50/60Hz (universal)
	Consumption	250W (typ)
CONTROLS	Basic	Standby/On, input, menu
	OnView [®]	Display mode, brightness, contrast, keystone, aspect ratio
		blank screen, gamma, white peaking, color temperature,
		user color, video (sharpness, saturation, tint), display (phase,
		tracking, H. position, V. position), advance (auto source
		select, rear, ceiling, eco mode, lamp hours, lamp reset,
		auto shutdown, OSD timeout, menu position, factory
		reset), audio (audio, mute)
OPERATING	Temperature	41–95°F (5–40°C)
CONDITIONS	Humidity	35–85% (non condensing)
NOISE LEVEL	Normal/Whisper mode	36 dB (typ); 34 dB (typ)
DIMENSIONS	Physical (mm)	256mm x 88mm x 200mm
(W x H x D)	Physical (in.)	10" x 3.8" x 7.9"
	Net	4.9 lb. (2.2 kg)
WEIGHT		
	Gross	11.0 lb. (5.0 kg)
REGULATIONS	Gross	UL, FCC-B, CCC, CE, NOM, PSB
REGULATIONS		. 0
REGULATIONS OTHER	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down,
REGULATIONS OTHER	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down, Projector, power cords, VGA cable, RCA video cable, S-video
WEIGHT REGULATIONS OTHER PACKAGE CON	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down, Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap,
REGULATIONS OTHER PACKAGE CON	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down, Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap ViewSonic Wizard CD, Quick Start Guide
REGULATIONS OTHER	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down, Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide Three-year limited warranty on parts and labor, first-year
REGULATIONS OTHER PACKAGE CON	whisper mode	UL, FCC-B, CCC, CE, NOM, PSB Vertical digital keystone correction, 3:2 pull down, Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***See ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12649-00B-10/05] PJ458D-1