## **PJ766D**

### HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR

WITH DIGITAL (DVI) CONNECTIVITY

## **Brilliant multimedia presentations**

ViewSonic's PJ766D is the class-leading multimedia DLP™ projector that delivers brilliant color, sharp graphics and outstanding video. The DIGITAL CLARITY OF DLP TECHNOLOGY GUARANTEES STUNNING LIFELIKE video and crisp data presentations. The native 1024x768 XGA resolution and an extremely high 2,500 lumens of brightness make it ideal for installations in conference rooms, religious sanctuaries, lecture halls and home theaters. The PJ766D offers multiple inputs including RGB, DVI-I, component, composite and S-video that ALLOW YOU TO CUSTOMIZE MULTIMEDIA PRESENTATIONS. Impress your audience with the power and performance of the PJ766D.



# DLP

#### POWER AND PERFORMANCE.

- > Bright in virtually any setting with 2,500 lumens Packs 2,500 lumens in just 7.9 lbs. It's the bright choice for mobile presenters.
- Supports HD signals including 720p and 1080i Capable of displaying HD signals as well as other video and data sources\*.
- > Easy set up and auto tuning

  Auto source dectection and auto sync.
- The perfect image in any setting Digital keystone correction, short focal length and zoom function ensure the perfect size image in any room.
- Whisper-mode extends lamp life Extend the life of your lamp up to 4,000 hours\*\* and reduce noise output.
- > Ultimate flexibility with multiple inputs
  Rich connectivity with RGB, DVI, component video, composite video and S-video inputs and a monitor ouput.
- > The best warranty in the business
  Covered by a three-year
  parts and labor limited
  warranty, first-year Express
  Exchange® and one-year
  limited lamp warranty.\*\*





## **PJ766D**

#### HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR WITH DVI







### Optional Accessories

• ATA hard shipping case
$\bullet$ Rolling soft case and laptop bag $\ \dots$ .PRJ-SCA-004
• Replacement lamp
• Universal ceiling mount kit WMK-005
• Extended Express Exchange®PRJ-EE-08-03

CACE 002

PROJECTOR	Туре	0.7" XGA Digital Micromirror Device (DLP™)
	Pixel Format	1024x768 XGA (native resolution)
	Lens	Manual zoom/ manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	37.5"–240" (diagonally)
	Throw Distance	58.8"-314.4"
	Throw Ratio	1.6–2:1
	Lamp	200W, 3,000 hours**
	Brightness	2,500 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
INPUT SIGNAL	Video	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i,
		720p, 1080i)
	Frequency	F <sub>h</sub> : 31–90kHz; F <sub>v</sub> : 50–85Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)
	Mac®t	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	DB-15 (x1)
	DVI (input)	DVI-I (x1)
	RGB (output)	DB-15 (x1)
	Composite Video (input)	
	S-Video (input)	Mini-DIN 4-pin (x1)
	Component Video (input) Control	
		RS-232 (mini-din, 3-pin)
	Audio (input)	Mini-Jack (x1); RCA (x1)
DOWER	Audio (output)	Mini-Jack (x1)
POWER	Voltage	90–240 VAC, 50/60Hz (universal)
	Consumption	255W (typ)
CONTROLS	Basic	Standby, menu, input, reset, H/V keystone
	OnView <sup>®</sup>	Main menu (brightness, contrast, sharpness, color temp,
		color saturation, color, tint, gamma, color space, reset),
		setup menu (H. position, V. position, keystone, aspect
		ratio, advance feature, reset), advanced feature menu
		(user color, white peaking, logo display, reset), configuration
		menu, utility menu, language menu, status menu
OPERATING	Temperature	41–95°F (5–35°C)
CONDITIONS	Humidity	5–95% (no condensing)
NOISE LEVEL	Normal	35 dB (typ)
	Whisper Mode	33 dB (typ)
DIMENSIONS	Physical (mm)	328mm x 88mm x 238mm
(W x H x D)	Physical (in.)	12.9" x 3.5" x 9.4"
• •		7 0 11 (0 ( 1 )
WEIGHT	Net	7.9 lb. (3.6 kg)
	Net Gross	7.9 lb. (3.6 kg) 14.3 lb. (6.5 kg)
WEIGHT		
		14.3 lb. (6.5 kg) UL/C-UL, FCC-B, TUV, CB, CCC, NOM
WEIGHT REGULATIONS		14.3 lb. (6.5 kg) UL/C-UL, FCC-B, TUV, CB, CCC, NOM
WEIGHT REGULATIONS		14.3 lb. (6.5 kg)  UL/C-UL, FCC-B, TUV, CB, CCC, NOM  Projector, power cord, VGA cable, remote control, lens cap ViewSonic Wizard CD, Quick Start Guide, S-video cable,
WEIGHT REGULATIONS		14.3 lb. (6.5 kg)  UL/C-UL, FCC-B, TUV, CB, CCC, NOM  Projector, power cord, VGA cable, remote control, lens cap ViewSonic Wizard CD, Quick Start Guide, S-video cable,
WEIGHT REGULATIONS		14.3 lb. (6.5 kg)  UL/C-UL, FCC-B, TUV, CB, CCC, NOM  Projector, power cord, VGA cable, remote control, lens cap ViewSonic Wizard CD, Quick Start Guide, S-video cable, DVI to HD-15 cable, soft carry case, ViewSonic Wizard CD Quick Start Guide
WEIGHT REGULATIONS CONTENTS		14.3 lb. (6.5 kg)  UL/C-UL, FCC-B, TUV, CB, CCC, NOM  Projector, power cord, VGA cable, remote control, lens cap ViewSonic Wizard CD, Quick Start Guide, S-video cable, DVI to HD-15 cable, soft carry case, ViewSonic Wizard CD



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Optional cables required. \*\*Running whisper-mode exclusively can extend lamp life. \*\*\*Visit ViewSonic.com for deatails. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP\* is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12658-00B-10/05] PJ452-1