

# Work Big IN42



## A force to be reckoned with.



When your colleagues need an IT miracle, they know you're the resident magician who can get it done. Your magic? Just some iron-clad trust in your projectors to perform each and every time. Your colleagues manage to impress audiences and clients with big presentations every day, and have complete confidence that their projector is up to the task. With the InFocus Work Big IN42, you share the feeling.

Crisp, clear pictures and bright, rich colors make for impressive images each and every time. Give your users the power to command an audience like never before with the IN42. This is a high-performance projector loaded with the features your colleagues want most. What you'll love is the rock-solid reliability and high-performance images you can count on time after time. With the IN42, your staff will present with power and confidence and you'll sleep better at night.

## An easy to use, icon-based remote allows you to quickly scroll and select your settings.



## Get some serious peace of mind.

Designed specifically for large meeting rooms and auditoriums, the IN42 offers all the features and connectivity you'll ever need. The IN42 includes RS232 and RJ45 connections, which enable seamless integration to your existing IT infrastructure, while the M1-DA and VESA connectors provide inputs for a variety of sources. Just the kinds of features you'd expect from the company that pioneered Systems-and Integration-class projectors.

### More lumens, brighter ideas.

Maybe you're thinking that all this networking capability comes at the expense of brightness—hardly. We dislike sacrifice as much as you do!

The IN42 boasts 3,500 max ANSI lumens—bright enough to leave the lights-on, or the window shades open during presentations. Upgraded LCD panels produce high contrast ratios and better color saturation to fully command an audience's attention. In addition, the ultraprecise manual zoom, focus and lens shift allow for the finest adjustability available.





## Form, function and features.

The IN42 features a new industrial design that's as alluring as the images it projects. As a protective measure the lens has been recessed, and a bright, intuitive LED feedback panel is built-in to keep all users informed.

#### Other features include:

- Quiet operation at <32dBA</p>
- → Top-mounted keypad for easy access to the standard projector adjustments you need
- → Business basic remote control
- Audible start-up/power-down cues
- → Tie wraps to ensure easy stowaway of both the power and data cables

Add it all up and you've got a projector that stands out from all the rest. Plus, with an affordable price point, the IN42 has a feature even the accounting organization will enjoy.

### **Enduring Quality**

If you're happy, InFocus is happy. That's why every InFocus projector comes with a standard one-year limited factory warranty (including parts and labor) and a six-month lampreplacement warranty.

For service program details in your region, please visit: www.infocus.com/service

### **Lens Options**

Fixed Short Throw Short Throw Long Throw Ultra Long Throw



### **Optional Accessories**

Ceiling Mount
Projection Screens
Performance Cables for Digital and HDTV
Cable Adapters
Advanced Remote Control

For more information about the IN42 or any InFocus business or home projector, optional accessories or service programs please visit: www.infocus.com

#### InFocus Corporate Headquarters:

27700B SW Parkway Avenue Wilsonville, Oregon 97070-9215, USA Phone: 503-685-8888 1-800-294-6400 Fax: 503-685-8887

#### In Europe

Strawinskylaan 585 1077 XX Amsterdam The Netherlands Phone: (31) 20 5792900 Fax: (31) 20 5792909 Freephone: 008000 4636287 (008000 INFOCUS)

#### In Asia

#07-01, Tanglin Shopping Centre 19 Tanglin Road Singapore 247909 Phone: (65) 6334-9005 Fax: (65) 6333-4525

©2006 InFocus Corporation. All rights reserved. InFocus, In Focus, INFOCUS (stylized), Play Big, Work Big, LP and SP are either registered trademarks or trademarks of InFocus Corporation in the United States and other countries. All other trademarks are used for identification purposes only and are the property of their respective owners in this and other countries. Part Number: 80

#### INFOCUS TECHNICAL SPECIFICATIONS\*

Native Resolution	XGA 1024 x 768
Display Technology	0.7" P.Si TFT LCD x 3 MLA
Input Sources	2xComputer (M1-DA and VESA); 3xVideo (Component YPrPb, S-Video 4-pin mini DIN, Composite RCA; 4xAudio (2x3.5mm/mini-jack for computer and 2xStereo RCA for Video); 4xControl Inputs (RS232, RJ45, USB (via M1-DA), 3.5 mm for Wired Remote)
Output Sources	Monitor Out (VESA); Line Level Stereo Audio (3.5 mm)
Computer Compatibility	VGA, SVGA, XGA, SXGA+, UXGA, Macintosh®
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i)
Brightness	3500 max ANSI lumens
Contrast Ratio	1000:1 w/Active Iris
Number of Colors	16.7 million
Projection distance	3.75' to 43.75'
Brightness Uniformity	95%
H-Synch Range	15-91 kHz
V-Synch Range	50-120 Hz
Dot Clock	13.5 MHz to 140 MHz
Digital Keystone Correction	+15/-5 degrees vertical correction; video/data
Projection Lens	Manual Focus and Zoom. Four alternate lenses available.
Zoom Ratio	1.2:1
Throw Ratio (distance/image width)	1.7:1-2.1:1
Minimum Projection Distance	3.75'
Image Offset Ratio %	100% Lens Shift for Vertical Keystone Correction. 9:1 to 1:1 offset
Aspect Ratio	4:3 Native. Will resize 16:9, 5:4
Image Size (diagonal)	30"-350"
Projection Methods	Front, ceiling, rear, rear ceiling
Audio	2 x 3W Stereo
Control	Projector keypad, IR remote control, USB via M1-D/A, RS232, RJ45
Lamp	285W UHP / 2000 hour user replaceable
Product Dimensions	5.11" H x 16.53" W x 12.4" D
Product Weight	13.2 lbs
Product Color	Black with Silver
Shipping Weight	23.2 lbs
Shipping Dimensions	9.17" H x 21.6" W x 18.5" D
Power Consumption	400W
Power Supply	100-240 Volts at 50-60 Hz
Operating Temperature	10-35°C at sea level to 7500' (2286 m), 50-95°F
Ships with	Computer cable (VESA w/tie wrap), power cable (w/tie wrap), remote control, user guide, detailed reference guide CD
Menu Languages	English, German, French, Italian, Spanish, Swedish, Portuguese, Russian, Chinese (simplified)
Audible Noise	32dbA Whisper Mode
Approvals	UL and c-UL (US/Canada), FCC-A (US/Canada), CE (CE member countries), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), C-Tick (Australia)

<sup>\*</sup> All specifications subject to change

<sup>\*\*</sup> Some resolutions may require Component/Vesa adapter

<sup>\*\*\*</sup> Resolution support may be product specific

<sup>\*\*\*\*</sup> Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.