

TOSHIBA

Start-up for professionals

s35

2,000 ANSI-lumens
Contrast 2,000:1



- High contrast ratio: 2,000 : 1
- Excellent picture quality in video and data mode
- ECO mode reduces the operating noise and expands lamp life
- 3 picture modes: brightness/standard/true colour



s35



- Display** 0.55" DDR DMD™* Chip
- Resolution** SVGA 800 x 600
- Brightness** 2,000 ANSI-lumens
- Colour reproduction** 16.7 mio. colours
- Contrast** 2,000 : 1
- Projection format** 4 : 3 switchable to 16 : 9
- Lamp** 180 W (TLPLV7LAMP)
- Max. lamp life** up to max. 2,000 hours/
up to max. 3,000 hours in ECO mode
- Lens** F = 2.0 - 2.15 / f = 19.40 - 22.50 mm,
manual zoom, focus
- Zoom** 1.2 x
- Frequency (hor./vert.)** 15 - 93 kHz / 50 - 85 Hz
- Projection** front, rear and ceiling
- Digital keystone correction** manual vertical
- Picture size (diagonal)** 0.76 m - 7.62 m
- Projection distance** 1.16 m - 10 m
- Input signals** NTSC / PAL / SECAM, 480i, 480p, 576i, 576p,
720p, 1,080i, VGA / SVGA, XGA / SXGA / UXGA (compr.)
- Inputs** 2 x RGB (D-sub 15), S-video, composite video (1 x RCA),
RGB audio (stereo mini jack), video audio (2 x RCA L/R)
- Outputs** RGB (D-sub 15), audio (stereo mini jack)
- Serial interface** RS-232C (mini DIN8 pin)
- Power supply** AC 100 - 240 V, 50 / 60 Hz
- Loudspeaker** 1 W (mono)
- Dimensions (W x H x D)** 285 x 98 x 254 mm
- Weight** 3.0 kg
- Specials** ECO mode, 3 picture mode
- Accessories** remote control with batteries, owners manual (CD ROM),
RGB- and power cable, softcase, lens cap
- Options** ceiling mounting, trolley, spare lamp



picture size (diagonal in m)	projection distance a (m)	
	min lenght (zooming max)	max lenght (zooming min)
0.76	1.16	
1.50	1.96	2.36
2.50	3.30	3.97
5.00	6.65	8.00
7.60	7.62	10.00