

# TOSHIBA

The bright  
business allrounder.

## t350 | tw350

3,500 ANSI-lumens  
Contrast 2,000:1  
XGA resolution  
tw350: wireless



- security-function protects from improper use (password and panel lock)
- Due to numerous connecting options perfect for conferencing and fixed installation
- tw350: WLAN capable with WLAN USB card (IEEE802.11b/g), PC card slot and LAN capable (RJ45)



## t350 | tw350



**Display** 0.7" DMD™\* Chip

**Resolution** XGA 1,024 x 768 (SXGA/UXGA compr.)

**Brightness** 3,500 ANSI-lumens

**Colour reproduction** 16.7 mio. colours

**Contrast** 2,000 : 1

**Projection format** 4 : 3 switchable to 16 : 9

**Lamp** 300 W (TLPLW13LAMP)

**Max. lamp life** up to max. 1,500 hours/

up to max. 2,000 hours in ECO mode

**Lens** t350: F = 2.4 - 2.6 / f = 23 - 27.6 mm,  
manual zoom and focus

tw350: F = 2.4 - 3.0 / f = 21 - 31.5 mm,

power zoom and auto focus

**Zoom** t350: 1.2 x, tw350: 1.5 x

**Frequency (hor./vertical)** 15 - 120 kHz / 30 - 150 Hz

**Projection** front, rear and ceiling

**Digital keystone correction** auto vertical / horizontal

**Picture size (diagonal)** t350: 0.85 - 7.62 m, tw350: 1.0 - 7.62 m

**Projection distance** t350: 1.3 - 12.1 m, tw350: 1.2 - 13.8 m

**Input signals** NTSC / PAL / SECAM, 480i, 480p, 576i, 576p,  
720p, 1.080i, VGA, SVGA, XGA, SXGA & UXGA (compr.)

**Inputs** DVI, 2 x RGB (D-sub 15), component video (1 x BNC),  
2 x audio (RCA L/R), 1 x S-video, composite video (RCA),  
3 x audio stereo mini jack

**Outputs** RGB (D-sub 15), audio (stereo mini jack)

**Serial interface** RS-232C (mini DIN8 pin), LAN (RJ45)

**Power supply** AC 100 - 240 V, 50 / 60 Hz

**Loudspeaker** 2 x 4 W stereo

**Dimensions (W x H x D)** t350: 340 x 115 x 314 mm,

tw350: 340 x 115 x 328 mm

**Weight** t350: 4.9 kg, tw350: 5.5 kg

**Specials** easy setup, security-function, black board-function,  
user logo, NCE2

tw350: USB, PC card slot

**Accessories** remote control with laserpointer and batteries, owners  
manual (CD ROM), quick reference, RGB und power cable,  
softcase

**Options** ceiling mounting, trolley, spare lamp, camera c001

**Wireless communication** (tw350) WLAN capable with WLAN USB card,  
wireless LAN (IEEE802.11b / g), 64/128 bit encoding, wep+



### t350

projection size (m)	projection distance (m)	
	min lenght (zooming max)	max lenght (zooming min)
0.76	1.30	-
1.50	1.90	2.40
2.50	3.30	4.00
5.00	6.60	8.00
7.62	9.90	12.00

### tw350

projection size (m)	projection distance (m)	
	min lenght (zooming max)	max lenght (zooming min)
1.02	1.17	1.79
1.52	1.77	2.71
2.54	2.99	4.55
5.08	6.03	9.16
7.62	9.06	13.76

Toshiba Europe GmbH

Projection & Display Technology

Phone: ++49-2131-158-01 · Fax: ++49-2131-158-835

e-mail: projektoreninfo@toshiba-teg.com