

# TOSHIBA



xd2000

Originals are detected  
by design and brilliance.

- attractive design
- High security (password function and panellock)
- easy set-up and „easy to use“



LCD stands for  
Liquid Cristal Display



## xd2000



## Immerse yourself in a world of colour.

**Display** 0,61" LCD Chip

**Resolution** XGA 1,024 x 768

**Brightness** 2,000 ANSI-lumens

**Colour reproduction** 16.7 mio. colours

**Contrast** 400 : 1

**Projection format** 4 : 3 switchable to 16 : 9

**Lamp** 210 W (TLPLW11LAMP)

**Max. lamp life** up to max. 2,000 hours/  
um to max. 3.000 hours in ECO mode

**Lens** F = 1.6 - 1.89 / f = 18.6 - 22.3 mm,  
manual zoom and focus

**Zoom** 1.2 x

**Frequency (hor./vertical)** 15 - 120 kHz / 30 - 150 Hz

**Projection** front, rear and ceiling

**Digital keystone correction** auto vertikal

**Input signals** NTSC / PAL / SECAM, 480i, 480p, 576i, 576p,  
720p, 1,080i, VGA / SVGA, XGA / SXGA / UXGA (compr.)

**Inputs** RGB (D-sub 15), S-video, composite video (1 x RCA),  
RGB audio (stereo mini jack), video / S-video audio (1 x RCA L/R)

**Outputs** RGB (D-sub 15), audio (stereo mini jack)

**Serial interface** RS-232C (mini DIN8 pin)

**Power supply** AC 100 - 240 V, 50 / 60 Hz

**Loudspeaker** 1 W mono

**Dimensions (W x H x D)** 295 x 81 x 255 mm

**Weight** 2.5 kg

**Operation noise** standard 34 dB / ECO mode 29 dB

**Specials** security-functions, user logo, password, panellock

**Accessories** remote control with batteries, owners  
manual (CD ROM), quick reference, RGB and power cable,  
softcase

**Options** ceiling mounting, trolley, spare lamp, camera c001

