

HITACHI

Inspire the Next

CP-RS56 series



- 1,600 ANSI Lumens
- 5.1 lbs.
- Vertical Keystone Correction
- RGB / Component / Composite / S-video Inputs
- RGB Input/Output x2/x1
- Contrast Ratio 500:1
- Auto Configuration (H-Size, Position)
- Approx. 3,000 Hour Lamp Life Whisper Mode
- Reverse Image Function for Ceiling Mount
- Gamma Correction
- Freeze Function
- Magnify (4x)
- 33dB (Whisper Mode)
- Native SVGA Resolution
- 2-3 Pull Down
- Throw Ratio 1.6-1.9:1
- Optical Zoom & Digital Zoom x 1.2

SPECIFICATIONS

Model Number		CP-RS56	
Liquid crystal panel structure		0.55" polysilicon active-matrix TFT x 3 with micro lens	
Resolution	Video	540 TV Lines	
	RGB	800 Dots x 600 Lines	
Colors		16.7 million colors	
Aspect ratio		Native 4:3; or 16:9 Compatible	
Lens		F1.6-1.9, Manual Zoom x 1.2, manual focus	
Throw ratio (distance:width)		1.6-1.9:1	
Lamp		165W UHB	
Brightness		1,600 ANSI Lumens	
Contrast Ratio		500:1	
Expected lamp life		Approx. 2,000 hours (Approx. 3,000 hours in Whisper Mode)	
Speakers		1Wx 1	
Power supply		AC100-120V/AC220-240V, 50/60 Hz, Auto Switching	
Power consumption		240W	
Approvals		UL60950/C-UL, FCC Class B, CE, EN60950	
Operating temperature		0 ~ 35°C (32° ~ 95°F)	
Inputs	RGB	VGA, SVGA, XGA, SXGA, UXGA MAC 16", 480i, 576i, 480p, 720p, 1080i	
	Composite Video Plug & Play	NTSC, NTSC4.43, PAL (-BGD), SECAM, PAL-M, PAL-N DDC1/2B	
Acoustic noise level		38dB (33dB in Whisper Mode)	
Vertical keystone correction		Digital Keystone +/- 15°	
Input/Output terminals	Data input	RGB	
	Data output	15-pin D-sub connector x 2	
	Video input	S-video	15 pin D-sub connector x1
		Composite video	Mini DIN 4-pin input connector x 1 RCA jack x 1
	Audio	input	Stereo mini jack x1
output		Stereo mini jack x1	
Control terminals		9-pin D-sub connector x 1 RS-232C (Serial)	
Chassis	Dimensions		
	Weight		
	Supplied accessories		
Replacement parts	Lamp		
	Remote control		
	Filter		



Screen Size 4:3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	32	63
60	48	79	95
80	64	105	127
100	80	132	158
120	96	158	190
150	120	198	238
200	160	264	318

Throw ratio: 1.6-1.9:1 (distance:width)

* Measured in inches

CP-RS56 Dimensions



(*) Excluding Lens and Leg