

HITACHI

Inspire the Next

CP-X260 series



3LCD

- 2,500 ANSI Lumens
- Native XGA Resolution
- 6.6lbs
- 2 RGB inputs and 1 RGB Output
- Component / Composite / S-Video Inputs
- HDTV Theater Ready
- FCC Class B
- Transition Detector
- Digital Gamma Correction
- Auto Vertical Keystone Correction
- Remote Control with "My Buttons"
- 34dB (Whisper Mode)
- Supplied Soft Case
- My Screen / My Memory
- Whiteboard Mode
- Blackboard Mode
- Approx. 3,000 hrs (Whisper Mode)
- Security Bar
- Kensington Security Slot
- Progressive Scan
- Audio Input / Output
- Input Source Naming

SPECIFICATIONS


Model name	CP-X260 series			
Liquid crystal panel structure	0.63" polysilicon active-matrix TFT x 3			
Number of pixels	786,432 pixels			
Resolution	Video	540 TV lines		
	RGB	1024 dots X 768 lines		
Colors	16.7 million colors			
Aspect ratio	Native 4:3/16:9 compatible			
Lens	F1.7 - 1.9 manual zoom 1:1.2			
Throw ratio (distance:width)	1.5 - 1.7:1			
Lamp	200W UHB			
Brightness	2,500 ANSI lumens			
Expected lamp life	Approx. 3,000 hrs (Whisper Mode) Approx. 2,000 hrs (Natural Mode)			
Contrast ratio	500 : 1			
Speakers	1W x 1			
Power supply	AC100-120V/AC220-240V 50/60Hz			
Power consumption	310W			
Operating temperature	5°C ~ 35°C (41°F ~ 95°F)			
Input signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"		
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N		
	Component video	480i, 576i, 480p, 720p, 1080i		
Acoustic noise level	39dB (34dB in whisper mode)			
H sync	15kHz ~ 106kHz			
V sync	50Hz ~ 120Hz			
Vertical keystone correction	Digital keystone +/- 30°			
Approvals	UL60950 / C-UL, FCC Part15, Class B			
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2	
	RGB output	RGB	15-pin D-sub connector x 1	
	Video input	S-video		Mini DIN 4-pin connector x 1
		Composite video		RCA jack x 1
		Component video		RCA jack x 3
	Audio	Input		Stereo mini jack x 2, RCA jack (L/R) x 1
Output			Stereo mini jack x 1	
Control terminals			9-pin D-sub connector x 1 (RS-232 control) USB connector (USB mouse) x 1	
Chassis	Dimensions	12.0" x 3.4" x 9.8" (W x H x D)		
	Weight	6.6 lbs.		
	Supplied accessories	Remote Control, Batteries (AA), RGB Cable, RCA Video Cable, Power Cord, Multiple Language Operator / Safety Manual, Soft Case, Security Label		
Replace-ment parts	Lamp	CPX260LAMP		
	Remote Control	HL02221		
	Filter	NJ22222		



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	84
80	64	93	112
100	80	117	140
120	96	140	169
150	120	176	211
200	160	234	282
300	240	352	423

Throw ratio: 1.5 - 1.7:1 (distance:width)
 *Measured in inches

CP-X260 Dimensions



(*) Excluding Lens and Leg